

FÉDÉRATION AÉRONAUTIQUE INTERNATIONALE

SPORTING CODE
SECTION 13 - SOLAR-POWERED AEROPLANES

covering
FAI aircraft Class CS (Solar-powered Aeroplanes)

~~2006~~ EDITION

This amendment is valid from ~~January 2006~~

Deleted: CIACA PROPOSAL

Deleted: 2005

Deleted: June 2005

FÉDÉRATION AÉRONAUTIQUE INTERNATIONALE

Avenue Mon Repos 24
CH 1005 - Lausanne
Switzerland

http://www.fai.org e-
mail: *sec@fai.org*

Copyright 2002-[2005](#)

All rights reserved. Copyright in this document is owned by the Fédération Aéronautique Internationale (FAI). Any person acting on behalf of the FAI or one of its members is hereby authorised to copy, print, and distribute this document, subject to the following conditions:

1. The document may be used for information only and may not be exploited for commercial purposes.
2. Any copy of this document or portion thereof must include this copyright notice.

Note that any product, process or technology described in the document may be the subject of other intellectual property rights reserved by the Fédération Aéronautique Internationale or other entities and is not licensed hereunder.

Rights to FAI international sporting events

All international sporting events organised wholly or partly under the rules of the Fédération Aéronautique Internationale (FAI) Sporting Code¹ are termed *FAI International Sporting Events*². Under the FAI Statutes³, FAI owns and controls all rights relating to FAI International Sporting Events. FAI Members⁴ shall, within their national territories⁵, enforce FAI ownership of FAI International Sporting Events and require them to be registered in the FAI Sporting Calendar⁶.

Permission and authority to exploit any rights to any commercial activity at such events, including but not limited to advertising at or for such events, use of the event name or logo for merchandising purposes and use of any sound and/or image, whether recorded electronically or otherwise or transmitted in real time, must be sought by way of prior agreement with FAI. This includes specifically all rights to the use of any material, electronic or other, that forms part of any method or system for judging, scoring, performance evaluation or information utilised in any FAI International Sporting Event⁷.

Each FAI Air Sport Commission⁸ is authorised to negotiate prior agreements on behalf of FAI with FAI Members or other entities as appropriate, of the transfer of all or parts of the rights to any FAI International Sporting Event (except World Air Games events⁹) which is organised wholly or partly under the Sporting Code section¹⁰ for which that Commission is responsible¹¹. Any such transfer of rights shall be by "Organiser Agreement"¹² as specified in the current FAI Bylaws Chapter 1, para 1.2 *Rules for Transfer of Rights to FAI International Sporting Events*.

Any person or legal entity which accepts the responsibility for organising an FAI Sporting Event, whether or not by written agreement, in doing so also accepts the proprietary rights of FAI as stated above. Where no formal transfer of rights has been established, FAI retains all rights to the event. Regardless of any agreement or transfer of rights, FAI shall have, free of charge for its own archival and/or promotional use, full access to any sound and/or visual images of any FAI Sporting Event, and always reserves itself the right to have any and all parts of any event recorded, filmed and/or photographed for such use, without charge.

¹ FAI Statutes, Chapter 1, para 1.6

² FAI Sporting Code, General Section, Chapter 3, para 3.1.3.

³ FAI Statutes, Chapter 1, para 1.8.1

⁴ FAI Statutes, Chapter 5, para 5.1.1.2; 5.5; 5.6 and 5.6.1.6

⁵ FAI Bylaws, Chapter 1, para 1.2.1

⁶ FAI Statutes, Chapter 2, para 2.3.2.2.5,

⁷ FAI Bylaws, Chapter 1, para 1.2.3

⁸ FAI Statutes, Chapter 5, para 5.1.1.2; 5.5; 5.6, 5.6.1.6

⁹ FAI Sporting Code, General Section, Chapter 3, para 3.1.7

¹⁰ FAI Sporting Code, General Section, Chapter 1, paras 1.2. and 1.4 ¹¹

FAI Statutes, Chapter 5, para 5.6.3

¹² FAI Bylaws, Chapter 1, para 1.2.2

**Fédération
Aéronautique
Internationale**

FAI Sporting Code

Section 13 - SOLAR-POWERED AEROPLANES

The FAI Sporting Code for Solar-powered Aeroplanes (the "Code") sets out the rules and procedures to be used to verify Solar-powered Aeroplanes (S -pA) flight performances. The essence of these rules is to ensure that a S-pA flight performance is achieved to a level of proof that is consistent for all flights. When processing the evidence supplied, Official Observers (OO) and the National Airport Control (NAC) should ensure that these rules are applied in the spirit of fair play and competition.

In this Code, a word or phrase appearing in small capital letters within the text of a chapter indicates that it has a distinct definition as it applies to the Code. In subsequent chapters the capitalisation is not used for these words or phrases.

References outside a chapter are by paragraph number.

Text in italic is informational in nature and not part of the rules and regulations of the Code.

Amendment list (AL) record

Formal amendments are published by the FAI Secretariat, acting for the Amateur-built & Experimental Aircraft Commission (CIACA) [on behalf of the Air Sport General Commission \(CAS\)](#). Within nations, the organisation responsible for National Airsport Control (NAC) for S-pA is then responsible for distributing amendments to all holders of Section 13 of the Sporting Code (SC13). This amendment list is for SC13 only - separate lists exist for the annexes to SC13.

A proposal for an amendment to the Sporting Code or its annexes must be submitted to the CIACA Bureau at least six months prior to the next CIACA Plenary meeting. A proposal must refer to the paragraphs affected and give reasons for the amendment. It is preferable for the proposed change to be in the format of the Code.

The Bureau will review the proposal and determine if it is "substantial" or otherwise. The Bureau will instruct the specialist sub-committee to process items that are clarifications of existing rules, or prepare discussion papers on substantial proposals for consideration at the next Plenary meeting. At the Plenary meeting, the philosophy behind a substantial amendment will be considered and set. The specialist sub-committee will then draft the Code amendment with Bureau feedback, and have it tested as required. The proposed amendment will then be published on the CIACA web site prior to the following Plenary meeting, at which time it will be submitted for final approval or rejection.

When amendments have been made to the text of the Code, a copy of the amendment list instructions should be inserted after this page so that, at a later date, the subjects of the amendment may be easily identified. Alternatively, users may download the amended Code from the document page of the FAI web site.

The latest amendments are indicated by a vertical line to the right of any paragraph that has been changed, as shown here.

TABLE OF CONTENTS

<i>paragraph</i>		<i>page</i>
	Chapter 1 General rules and definitions	
1.0	General	0
1.1	Definition of flight terms	1
1.2	Definition of Solar-powered Aeroplanes flight measurement terms	2
1.3	Other definitions	2
1.4	Types of Solar-powered Aeroplanes flight performances	3
	Chapter 2 Solar-powered Aeroplanes World records	
2.0	General	5
2.1	Record categories, classes, and types	5
2.1.4	Table 1 - Types of record flights	6
2.2	Time limits on record claims	6
	Chapter 3 Verification requirements and methods	
3.1	Flight data requirements	7
3.2	Declaration	7
3.3	Flight data verification	8
3.4	Calculations and calibrations	9
3.4.3	Table 2 - Minimum data requirements	10
3.4.4	Table 3 - Minimum accuracy requirements	10
3.5	Time measurement and evidence	11
3.6	Position measurement and evidence	12
3.7	Altitude evidence and control	15
3.8	Means of propulsion/Source of Energy evidence and control	16
	Chapter 4 Official Observers	
4.1	Authority	18
4.2	Certification of events	19
	Chapter 5 Certificates and proofs	
5.0	General	20
5.1	Barogram ...	20
5.2	Landing certificate	20
5.3	Barograph calibration certificate	20
5.4	Timing device calibration statement	20
5.5	FAI record claim forms	21

Chapter 1

GENERAL RULES and DEFINITIONS

1.0 GENERAL

- 1.0.1 The General Section (GS) of the Sporting Code contains general definitions and rules applying to all air sports. This Section (SC13) gives specific rules that apply to Solar-powered Aeroplanes (S-pA) (GS 1.4 AL2 Class CS).

The maturity of this kind of aeroplane is still quite limited and, most likely, they will remain, for some years, a small number of experimental machines. For this reason, for the time being, this section of the FAI Sporting Code deals with the record breaking rules only. Subsequent editions, when necessary, will include also rules for S-pA competitions.

Deleted: -
Deleted: s

- 1.0.2 Terms, rules, and requirements are defined first in their most general sense. Where an exception to a general rule exists, it will be described in the paragraph of the Code where the exception occurs.

- 1.0.3 AIRCRAFT : A vehicle that can be sustained in the atmosphere by forces exerted on it by the air.

Deleted: up

- 1.0.4 AERODYNE : A heavier-than-air aircraft, that can be dynamically sustained in the air by the reaction of the air upon surfaces in relative movement.

Deleted: An aircraft,
Deleted:
Deleted:

- 1.0.5 AEROPLANE : A fixed wing aerodyne with means of propulsion.

- 1.0.6 SOLAR-POWERED AEROPLANE (S -pA) : An aeroplane which can be sustained in level flight in the atmosphere using solely sun-light energy impacting on its airframe as its energy source. (Energy can be stored, both before flight and during flight, into on-board energy storage system)

Deleted: or

- 1.0.7 METHOD OF PROPULSION/SOURCE OF ENERGY (MoP/SoE) : Solar-powered Aeroplanes shall not make use of sources of energy other than that of sun-light impacting on their airframes and converted by their on-board photo-voltaic system, for propulsion or for any other purpose. (e.g.: a "non autonomous take-off would be a reason for a S-pA to be included in the "Assisted" sub-class)

Deleted: for propulsion, neither for any other purpose,
Deleted: different from

SUB-CLASS "ASSISTED": Solar-powered Aeroplanes which, during a part of the flight other than the flight performance, make use of sources of energy other than that of sun-light impacting on their airframes and converted by their on-board photo-voltaic system, for propulsion or for any other purpose.

Deleted: ir
Deleted: not aimed at record and/or competition
Deleted: , for propulsion or for any other purpose,
Deleted: different from

1.1 DEFINITION of FLIGHT TERMS

- S-pA FLIGHT PERFORMANCE** 1.1.1 the performance during that portion of a S-pA flight from the START POINT to the FINISH POINT. Means of Propulsion/Source of Energy shall be in line with Para. 1.0.7.
- WAY POINT** 1.1.2 A precisely specified point or point feature on the surface of the earth using a word description and/or a set of coordinates. A WAY POINT may be a START POINT, a TURN POINT, or a FINISH POINT and has an associated OBSERVATION ZONE.
- LEG** 1.1.3 The portion of a flight between two successive WAY POINTS.
- COURSE** 1.1.4 The line joining all successive WAY POINTS of an S-pA FLIGHT PERFORMANCE.
- OBSERVATION ZONE** 1.1.5 The area over which an S-pA must pass to verify that a WAY POINT has been reached (see 3.6.2e). It is a 90 degree sector, having no upper limit, with its apex at the WAY POINT. This sector is:
- a. For a TURN POINT, symmetrical to and remote from the bisector of the inbound and outbound LEGS of the TURN POINT,
 - b. For a START POINT, symmetrical to and remote from the outbound LEG,
 - c. For a FINISH POINT, symmetrical to and remote from the inbound LEG.
- START** 1.1.6 The beginning of the S-pA FLIGHT PERFORMANCE. It must be either:
- a. The moment when means of propulsion and/or sources of energy different from those allowed are switched-off ("Assisted" Sub-Class only, see also 1.0.7.) or
 - b. Leaving the OBSERVATION ZONE of a START POINT, or
 - c. Crossing a START LINE.
- START POINT** 1.1.8 The WAY POINT marking the start of an S-pA FLIGHT PERFORMANCE. It must be either:
- a. A WAY POINT declared as a START POINT, or
 - b. The midpoint of a START LINE.
- START LINE** 1.1.9 A horizontal line one kilometre in length, oriented approximately perpendicular to the first LEG. The midpoint of the line (the START POINT) is at ground level.
- TURN POINT** 1.1.10 A WAY POINT between two LEGS of a flight.
- FINISH** 1.1.11 The end of the S-pA FLIGHT PERFORMANCE. It must be:
- a. By landing the S-pA, or
 - b. The S-pA enters the OBSERVATION ZONE of the FINISH POINT, or
 - c. Crossing a FINISH LINE, or
 - d. Starting a ~~non~~-allowed means of propulsion and/or source of energy ("Assisted" sub-class only, see also 1.0.7.)
- FINISH POINT** 1.1.12 The WAY POINT marking the end of an S-pA FLIGHT PERFORMANCE. It is:
- a. The point at which the nose of the S-pA comes to rest after landing, or

Deleted: either

Deleted: not

- b. A WAY POINT declared as the FINISH POINT, or
- c. The midpoint of a FINISH LINE, or
- d. The point at which a non-allowed means of propulsion and/or source of energy is started ("Assisted" sub-class only, see also 1.0.7.)

Deleted: not

FINISH LINE 1.1.13 A horizontal line one kilometre in length, oriented approximately perpendicular to the final LEG. The midpoint of the line (the FINISH POINT) is at ground level.

1.2 DEFINITION of S-pA FLIGHT PERFORMANCE MEASUREMENT TERMS
Depending upon the type of flight, the following parameters may be determined to assess an S-pA FLIGHT PERFORMANCE. The requirements for gathering flight measurements and the precision of measurement are given in Chapter 3.

Deleted: -

OFFICIAL DISTANCE 1.2.1 The length of the COURSE in the sequence of the LEGS used, minus any applicable HEIGHT PENALTY (1.2.9).

Deleted: possible

START TIME 1.2.2 The time that the S-pA FLIGHT PERFORMANCE starts.

START ALTITUDE 1.2.3 The altitude of the S-pA above sea level at the START.

FINISH TIME 1.2.4 The time that the S-pA FLIGHT PERFORMANCE finishes.

FINISH ALTITUDE 1.2.5 The altitude of the S-pA above sea level at the FINISH.

DURATION 1.2.6 The time elapsed between the START TIME and the FINISH TIME .

LOSS OF HEIGHT 1.2.7 The START ALTITUDE minus the FINISH ALTITUDE (see also 1.4.7).

GAIN OF HEIGHT 1.2.8 The difference between the maximum altitude and a previous minimum altitude during the S-pA FLIGHT PERFORMANCE.

HEIGHT PENALTY 1.2.9 A distance equal to 100 times the excess over 1000 metres LOSS OF HEIGHT. (See 3.4.2 for how the penalty is applied.)

1.3 OTHER DEFINITIONS

OFFICIAL OBSERVER 1.3.1 The Official Observer (OO) is the person who has the official control of flights undertaken for FAI record attempts and of the data gathered to prove a S-pA FLIGHT PERFORMANCE (see chapter 4).

DECLARATION 1.3.2 The official description of the task and other data as listed and defined in 3.2.

BAROGRAPH 1.3.3 A recording device measuring external air pressure.

BAROGRAM 1.3.4 The trace, recording, or electronic data output of a BAROGRAPH.

FLIGHT RECORDER 1.3.5 An electronic device which has been approved by the CIACA to record data, including position and altitude, during a flight (such as a GNSS flight recorder).

MoP/SoE RECORDER (Sub- Class "Assisted" only)

1.3.6 A device that either:

- a. Records the time and altitude of any operation of the non-allowed MoP or a change in the energy consumption system configuration of the S-pA, or
- b. Records the fact that the non-allowed MoP/SoE is not being used. It must operate in such a way that failure of the device will indicate that the non-allowed MoP/SoE is being used.

Deleted: not

Deleted: not

Deleted: not

GEODESIC

- 1.3.7 (Also geodesic line and geodesic distance.) The shortest distance between two points on the surface of an ellipsoidal world model. See also 3.4.1.and annex C Appendix 2.

1.4 TYPES of S-pA FLIGHT PERFORMANCES

Deleted: PERFORMANCE

1.4.1 General requirements

- a. An S-pA FLIGHT PERFORMANCE may be claimed for
 - absolute altitude
 - duration
 - distance
 - speed around the world, non-stop,
 - speed around the World (not for "Assisted" sub-class)
- b. An S-pA FLIGHT PERFORMANCE may be claimed from any flight which meets the requirements of proof for that performance.
- c. A DECLARATION is required except where specifically not required in the rules.
- d. WAY POINTS must be declared and used in the sequence declared except where specifically not required in the rules.

Deleted: and non-refuelled

1.4.2 Altitude and duration performances

No DECLARATION is required.

- a. ABSOLUTE ALTITUDE
An S-pA PERFORMANCE measured for maximum altitude achieved. An absolute altitude performance is valid only if preceded by a GAIN OF HEIGHT of at least 5000 metres.
- b. DURATION
An S-pA FLIGHT PERFORMANCE measured for DURATION .

1.4.3 Distance performance

The WAY POINT(S) of distance record flight performance must be declared preflight. The three distance record types are:

- a. STRAIGHT DISTANCE
A flight from a START POINT to a FINISH POINT with no TURN POINTS.
- b. OUT AND RETURN DISTANCE
A CLOSED COURSE flight having one TURN POINT.

Deleted: FLIGHT

c. DISTANCE ALONG A COURSE

A flight from a START POINT via up to three TURN POINTS to a FINISH POINT. The TURN POINTS must be at least 50 kilometres apart .

1.4.7 Loss of height - alternate calculation for distance flights

A distance flight (1.4.3) starting as defined in 1.1.8b (a declared START POINT) may be claimed where the LOSS OF HEIGHT (1.2.7) is measured from the start point height to the elevation of the finish point.

1.4.8 Speed around the world, non-stop

The course, including suitable control points (to be dealt with as WAY POINTS), shall be approved in advance by the NAC's concerned (Control points shall be chosen from a pre-defined list of possible way -points). It must start and finish at the same aerodrome, crossing all meridians. The length of the course shall not be less than 36 787.559 kilometres (equal in length to the Tropic of Cancer).

If, for any reason, final landing cannot be made at the aerodrome of departure, the aeroplane may fly to an alternate landing place lying beyond the original one (at a greater distance from which the start was made).

The start time shall be the time of take-off; the finish time shall be the time of landing.

1.4.9 Speed around the World (Not for "Assisted" sub-class)

The course, including suitable control points (to be dealt with as WAY POINTS), shall be approved in advance by the NAC's concerned (Control points shall be chosen from a pre-defined list of possible way -points). It must start and finish at the same aerodrome, crossing all meridians. The length of the course shall not be less than 36 787.559 kilometres (equal in length to the Tropic of Cancer).

All control points must be at latitude of less than 66° 33' (outside the North and South Frigid Zones).

If, for any reason, the final landing cannot be made at the aerodrome of departure, the aeroplane may fly to an alternate landing place lying beyond the original one (at a greater distance from which the start was made).

Intermediate landing places shall coincide with the subsequent take-off place.

Any time spent on the ground between start and finish shall be counted as flying time.

Repairs or replacements of aeroplane components and engine(s) are permitted except that the wings and fuselage may not be changed.

Pilot(s) may not be changed during the attempt.

The start time shall be the time of take-off; the finish time shall be the time of landing.

Deleted: that

Deleted:

Deleted: In the case that pilots change along the performance, another kind of record can be attributed to the specific aeroplane "team".

Chapter 2

SOLAR-POWERED AEROPLANES WORLD RECORDS

This chapter defines all the FAI world records for Solar-powered Aeroplanes and the general handling of world record claims. General rules relating to FAI records are in the General Section of the Sporting Code.

2.0 GENERAL

FAI world Solar-powered Aeroplanes record attempts require no advance notice provided that arrangements have been made for controlling the flight (4.1.2 and 4.1.3).

2.0.1 FAI Sporting Licence

The pilot must possess a valid FAI Sporting Licence (GS 8.1) in order to attempt and to claim an FAI world record.

2.0.2 Records in any one flight

Any record or records may be broken in any one flight for which the requirements are met.

2.0.3 Verification of world records

World Records must be verified with the evidence of a CIACA approved flight recorder or with other techniques previously accepted by CIACA. (See 1.3.5).

2.1 RECORD CATEGORIES, CLASSES, and TYPES

Record categories are concerned with the pilot, record classes, with the Solar-powered Aeroplane, and record types with the nature of the Solar-powered Aeroplane flight performance.

Deleted: ,

In the case of a Speed around the World record (not for "Assisted" sub-class) performed by more than one pilot, the record can be attributed to the specific aeroplane "team".

2.1.1 Pilot categories

There is a General category for all pilots. No Feminine category exists.

Deleted: is considered

2.1.2 Aeroplane classes

World records are recognised in the classes listed in 1.0.7.

2.1.3 Designation of records

Solar-powered Aeroplane records are designated by code letters, starting with the FAI code letter for Aeroplane (C), then the Solar-powered class (S) and, if applicable, the sub-class "Assisted" (A).

Examples: CS - Solar-powered Aeroplane
CSA - Solar-powered Aeroplane "Assisted" sub-class

Chapter 3

VERIFICATION REQUIREMENTS and METHODS

This chapter defines the evidence, measurements and calculations required to verify Solar-powered Aeroplane performances.

3.1 FLIGHT DATA REQUIREMENTS

The following is a list of all the flight data that needs to be gathered or measured to provide evidence of the completion of any Solar-powered Aeroplane performance:

- a. declaration (1.3.2)
- b. start point (1.1.8)
- c. start time (1.2.2)
- d. start altitude (1.2.3)
- e. way point(s) (1.1.12)
- f. finish time (1.2.4)
- g. finish altitude (1.2.5)
- h. maximum altitude (1.4.2a)
- i. gain of height (1.2.8)
- j. flight continuity (3.3.3)

Different flight performances will require different subsets of this list.

3.2 DECLARATION

For each flight, certain information is required to be recorded before the flight in order to ensure that proof of the SpA Flight performance is available after the flight. This data, including [way points](#) (e) is known as the declaration. For some performances, some data is not required, but the Official Observer must ensure that all required data is recorded.

Deleted: way

3.2.1 Declaration content

The information shall be written on a single sheet of paper or board, or recorded in the memory of a flight recorder prior to the flight.

- a. Date of flight
- b. Name of pilot
- c. Type and registration of S-pA
- d. Type, serial number or other identification document of barograph or flight recorder (1.3.5)
- e. Way points and the sequence to be flown, start, turn(s), finish as applicable to the specific flight performance
- f. Date and time of declaration
- g. Signature of pilot (not required for electronic declarations)

3.2.2 Declaration validity

- a. The last declaration made before takeoff is the only one valid for the flight.

- b. If a declared turn point is abandoned, a distance along a course flight may still be claimed from the resulting shorter course provided that the turn points achieved are in the sequence specified in the declaration.

3.3 FLIGHT DATA VERIFICATION

3.3.1 Flight data collection

A barograph or device incorporating a barograph must operate throughout the flight. The barogram so produced must provide indisputable verification of flight continuity (see 3.3.3) and of all altitudes critical to the flight performance. The device may record parameters in addition to barometric pressure and time if it is suitable for the purpose (see 3.4). If data is recorded at intervals, the sampling rate setting must be no slower than once per minute.

For flight recorders, timing and pressure altitude data will be taken at the boundary of the observation zone interpolated between the times of valid fixes; or for a start or finish, this data may be taken from the fix in the observation zone which is most favourable to the pilot.

3.3.2 Landing

The landing location must be certified by one or more of the following:

- a. By an OO present or arriving soon after the event and there is no doubt about the position of landing or,
- b. By two witnesses (see 4.2.3c),
- c. By position data from a flight recorder (but see also 3.6.4a(ii)).

3.3.3 Flight continuity

There must be evidence that the S-pA did not land or (for "Assisted" sub-class only, see 1.0.7.) no means of propulsion/source of energy different from those allowed was used during the claimed flight performance. An interruption in the barogram data will not compromise proof of flight continuity provided that the OO and NAC are convinced no critical data is missing and that the evidence for flight continuity remains indisputable.

In the event of failure of the pressure altitude recording in a flight recorder, evidence of flight continuity may be assessed from a time plot of GNSS calculated altitudes provided the rule on the setting of sampling rates is followed (3.3.1).

3.3.4 Altitude

Absolute altitude, gain of height and start altitude must normally be verified from atmospheric pressure data recorded by a barograph. External measurement (see 3.7.1) may be used only when the required accuracy can be verified.

3.4 CALCULATIONS and CALIBRATIONS

Time, geographical position, altitude, and means of propulsion/source of energy are flight performance data which must be either recorded or measured for some or all types of flights. Using this data, calculations of distance, duration, gain of height, altitude difference, height penalties and start height may be done.

3.4.1 Calculations for distance and speed

For world records, distances between two points in excess of 1000 kilometres, and in any case of dispute over a distance, the distance flown is deemed to be the length of the geodesic line joining the start point and the finish point or, if there are turn points, the sum of the geodesic lines for each leg of the course.

a. EARTH MODEL TO BE USED

For the purpose of the calculation of FAI geodesic distances, the WGS 84 earth model shall be used.

When calculation of the exact distance is not critical, less accurate methods may be used.

b. GEOGRAPHICAL COORDINATES OF WAY POINTS

NACs are to specify procedures for recording the geographical coordinates of way points from maps of their national territory using geographical co-ordinates such as Latitude and Longitude, map grid, or national grid (if such a grid exists for the area concerned).

c. MAP SCALES

Measurement of co-ordinates of way points should be from a map with a scale at least as detailed as 1:250,000, and preferably 1:50,000 (if such a map exists which includes the way point concerned). If a scale less detailed than 1:50,000 was used, the NAC should be able to show that co-ordinates were taken from the most accurate map available for the way point concerned.

3.4.2 Loss of height and application of the height penalty

- a. For distance flights of more than 100 kilometres, where the loss of height (1.2.7) exceeds 1000 metres, a height penalty (1.2.9) must be subtracted from the length of the course to give the official distance.
- b. For distance flights of 100 kilometres or less, a loss of height exceeding 1% of the length of the course will invalidate the flight performance.
- c. For duration flight a loss of height exceeding 1000 metres will invalidate the flight performance.

3.4.3 Flight data requirements

The minimum flight data required for each type of flight performance is given in Table 2.

Table 2 Minimum data requirements						
Flight Performance	Measurements			Calculations		
	Time Position Height		MoP/SoE Distance Height			
Distance	x	x	x	x	x	x
Duration	x		x	x		x
Altitude	x		x	x		x

3.4.4 Accuracy of measurement

The minimum accuracy of measurement and calculation required for each type of flight data is given in Table 3. Any inaccuracy in a measurement or calculation is to be interpreted to the maximum disadvantage of the pilot.

Table 3 Minimum accuracy requirements						
Flight Performance	Measurements			Calculations		
	Time	Position Height	MoP/SoE	Distance	Height	
Distance	1 min	500 m	active	1 km	30 m	
Duration	1 min		active		30 m	
Altitude	1 min	1%	active		10 m	

Precision of measurement

Care should be taken to correctly assess the precision of measurement devices so that an invalid level of accuracy is not introduced into calculations.

3.4.5 Combinations of measurement methods

Any combination of the measuring methods is acceptable for the various types of flights, provided the minimum requirements for accuracy of equipment in paragraphs 3.4.3 and 3.4.4 are fulfilled.

Each method used must comply with this Code as if it were the only means of proof employed.

3.4.6 Timing device calibration

When used, clocks and other time recording equipment shall be checked against official time signals both immediately before and again after the flight, covering a period of at least three hours. Any error found shall be taken into account and rounded up in the calculations. The GNSS time recording from a flight recorder may be used as an official time signal.

3.4.7 Barograph calibration period

Barograph calibrations are required to ensure that the measurement of barometric pressure and time are checked against, and corrected as necessary, to official standards. For records, both (a) AND (b) calibrations below are required, and the least favourable calibration of the two shall be used making the calculations for the record.

a. PRIOR TO THE FLIGHT

The calibration used must have been performed within 12 months prior to the flight or, for CIACA -approved electronic barographs and flight recorders, 24 months.

b. AFTER THE FLIGHT

The calibration used must have been performed within one month after the flight.

3.4.8 Calibration correction

When absolute altitude (not altitude difference) is to be determined, the altitudes reached during a flight from the barograph evidence must be corrected for a height error arising from the actual atmospheric pressure of the day compared to the standard atmosphere.

3.5 TIME MEASUREMENT and EVIDENCE

3.5.1 Time measurement

Time data requirements may be fulfilled by any of the following measuring methods:

- a. By direct observation from the ground by an observer with direct access to approved time measuring equipment (e.g. a synchronised timepiece). If a time piece displaying only minutes is used, 59 seconds is to be added to each duration measured to allow for the possibility that the reading was taken just before the minute changeover. Pilots and OOs should use timing devices with outputs in seconds whenever possible.
- b. With a barograph, to measure time differences,
- c. With a time camera, to measure time differences (except for duration flights),
- d. A recording device with correct real time input, such as a flight recorder.

3.5.2 Time evidence

- a. Evidence of timing and time recording of flights must be under the control of an OO. Time recording equipment carried on board a S-pA must be capable of being physically or electronically sealed and, where a human action is required, shall be sealed and unsealed only by the OO.
- b. The equipment must be positioned so that the time parameters cannot be altered by the pilot or passenger during the flight.
- c. If a means is provided for the pilot to make inputs into a device for remote recording of flight events, such inputs must be confined to functions not critical to the validation of the flight.

For example, it is permissible for a pilot to make a mark on the time base to register an event such as a particular position, or in GNSS systems to change the sampling rate in flight.

3.5.3 **Night flight**

In the case of a flight which continues beyond the hours of legal daylight in the country concerned the Solar-powered Aeroplane and pilot shall comply with the laws of that country for night flight or a specific dedicated permission shall be obtained.

3.6 **POSITION MEASUREMENT and EVIDENCE**

3.6.1 **Position measurement**

Flight position data requirements may be fulfilled by any of the following measuring methods:

- a. By direct observation from the ground for start, turn, and finish points,
- b. Satisfactory photographic evidence from a camera in the S-pA;
- c. Satisfactory data from a flight recorder in the S-pA.

3.6.2 **Position evidence - general**

- a. **CROSSING A START LINE**
 - (i) When the start line is controlled by observation from the ground, visual observation of a crossing in the direction of the first leg at an altitude of not more than 1000 metres above the line.
 - (ii) When using flight recorder evidence, by clear proof that the start line was crossed in the direction of the first leg.
- d. **CROSSING A FINISH LINE**
 - (i) When the finish line is controlled by observation from the ground, the nose of the Solar-powered Aeroplane crosses the finish line unassisted from the direction of the last leg at a height of not more than 1000 metres above the line.
 - (ii) When using flight recorder evidence, by clear proof that the finish line was crossed from the direction of the last leg.
- e. **WAY POINTS**

Way points should be of such a nature that they are easily recognisable from the air. Where photography is used, way points shall be point features and should be selected to make interpretation of photographs easy, even on photographs taken in difficult light conditions such as low contrast. Where a flight recorder is being used for verification, the way point co-ordinates do not need to represent a point feature on the ground.
- f. **OBSERVATION ZONE**

Evidence is required that the S-pA was within the observation zone (1.1.5) of a way point used during the flight. This may be collected by using one or more of the following three methods:

- (i) Direct observation, in which the S-pA is positively identified as being within the observation zone by an OO on the ground at the turn point. Magnification and tracking devices may be used.
- (ii) Photographic, where the pilot presents a satisfactory photograph taken from within the observation zone in accordance with the rules for photographic evidence below.
- (iii) Flight recorders, where (in accordance with the CIACA rules for the use of this equipment (see 3.6.4)), the data record shows incontrovertible proof that the S-pA was in the observation zone, with one position fix recorded either exactly on the position of the way point or within the observation zone, or else a straight line drawn between two consecutive valid fixes crosses the observation zone.

Deleted: way

3.6.3 Photographic position evidence

Photographs can be used to prove evidence of position and generally substantiate the S-pA performance by means of a sequence of photographs on a single length of film. There shall be proof that all pictures were taken from the aeroplane on the flight concerned and that turn point(s) were photographed between the start time and finish time.

a. PHOTOGRAPHIC CONTROL METHOD

The following method shall be used:

- (i) Mounting in the cockpit
The camera must be held in fixed mountings in the cockpit so that every photograph will show the wingtip. The lens housing should be positioned inside the canopy or camera window so that the random line mentioned in (iii) below will show on the film.
- (ii) Sealing the camera
The camera must be sealed unless the same OO is controlling both the preflight photograph(s) and the processing of the film, in which case sealing is not necessary. When a time recording camera is used to supply time evidence, it must be sealed by an OO before the flight in such a way that the film cannot be removed and the time adjusting mechanism cannot be accessed until the seal is broken by an OO after flight.
- (iii) Before takeoff
Just prior to takeoff an OO shall mark the outside of the canopy or window across the front of the lens with a random line and display the flight declaration for the pilot to photograph with the camera installed.

The random line should be dark or opaque and at least 3 mm wide if it is to show on the image.

- (iv) After flight
Following landing and the completion of the photographic sequence, an OO shall take charge of the film and have it developed. Every effort is to be made to preserve the film as a continuous strip. However, if it is cut or broken while out of control of the pilot or OO, this evidence remains valid if close examination of the pieces show that they form the original continuous length of film. An OO shall describe the circumstances under which the film was broken or cut.

b. PHOTOGRAPH SEQUENCE

The film shall contain photographs in the following sequence:

- (i) the pre-flight clock synchronisation photo(s) if a time camera is used (see 3.5.1c and 3.5.2a),
- (ii) the declaration,
- (iii) at least one photograph showing indisputable evidence of the presence of the Solar-powered Aeroplane in each of the observation zone(s) of the way point(s) used, in the correct sequence,
- (iv) the S-pA on the landing field with surrounding features and its registration markings appearing clearly on the photo, or the above declaration with landing time added.
- (v) the post flight synchronisation photo(s) if a time camera is used.

Photographs in (ii) and (iii) above must show the shape of the canopy mark (see 3.6.3a(iii)) on the film image. Additional photographs which may have been taken after the declaration and before the landing must also show the canopy mark.

3.6.4 **Flight recorder (GNSS) position evidence**

All flight recorder evidence must be produced by an FAI/CIACA approved system. The WGS84 Geodetic Datum shall be set for all Lat/Long data that is recorded and transferred after flight for analysis.

a. FLIGHT RECORDER CONTROL METHOD

The OO shall familiarise himself with the terms of the approval for the GNSS and flight recorder equipment concerned. There must be incontrovertible evidence, independent of the FR data, that the FR from which the flight data was taken was in the S-pA flown by the pilot during the claimed flight performance.

- (i) Before the flight
The OO shall sign the pilot's written flight declaration, except where the declaration is stored electronically in the flight recorder (1.3.2). The OO shall enter a secret code into the flight recorder if the CIACA approval for the equipment requires this. The flight recorder system shall be placed, configured or sealed in such a way that it will be physically impossible to operate any controls other than those specifically allowed for use in flight; and to connect or disconnect any device to the flight recorder system other than in accordance with the CIACA approval for the equipment. The method(s) of sealing, if any, shall be specified in the CIACA approval for the equipment.
- (ii) Takeoff and landing
An OO shall ensure that there is evidence for the times and points of takeoff and landing, pilot(s) names, aeroplane type and registration, and the type and serial number of the FR for flight evidence. This evidence shall be independent of the data produced by the FR.
- (iii) After flight
After landing, the flight data shall be transferred from the FR to a diskette via a PC or other device in the manner specified in the CIACA approval for the

equipment. The OO shall check any seals which were applied before the flight. The diskette containing the flight data shall then be sent to a person approved by the NAC to make the analysis.

b. DATA ANALYSIS

The analysis of the flight data shall be performed by a qualified person approved by the NAC, whose duty is to ensure that the appropriate evidence is present to verify the attainment of way points, heights, times and position, as required. If the flight performance qualifies for a record, the following shall be forwarded to the NAC:

- (i) The original data diskette (the first copy) storing the flight data. This must include the data file in the CIACA recommended format, and the file in its original format, (if different) as transferred from the flight recorder immediately after landing.
- (ii) The appropriate claim form(s), including OO's evidence that manually recorded times and exact locations correspond to the equivalent flight recorder data.
- (iii) For record flights, the achieved way points shall be determined from the flight recorder evidence and specified in the claim for the record. The flight recorder "pilot event marker", if incorporated, may be used to indicate the desired way point position(s).
- (iv) Any other measured data and/or auxiliary material required by an NAC to support the mandatory evidence.

Deleted: ¶

Deleted: way

Deleted: a

3.7 ALTITUDE EVIDENCE and CONTROL

3.7.1 Altitude evidence

Altitude data requirements may be fulfilled by any of the following measuring methods:

- a. A barogram,
- b. Optical measurement from the ground (e.g. a suitable height frame or theodolite),
- c. Radar measurement from the ground,
- d. For continuity of flight purposes only, the GNSS altitude output of a flight recorder.

3.7.2 Altitude control methods

For altitude recording other than by external measurement, a barograph or flight recorder must be carried in the aeroplane. Any marking of the barogram during flight shall be done by remote control, not by direct access to the barograph itself. The barograph shall be placed in the S-pA in such a way that no part of the barograph is accessible to the pilot or passenger during the flight.

The pressure altitude recording system in a flight recorder is a barograph and must comply with other rules in the Code for barographs and their calibration. Altitude control methods for flight recorders are the same as those used for position evidence (see 3.6.4).

a. BEFORE TAKEOFF

- (i) Mechanical barographs

The OO shall make an identification mark on the barogram paper/foil and then seal the barograph.

(ii) Electronic barographs

The OO shall seal the barograph and then enter a secret multi-character code into the barograph memory before flight (a second entry of this code shall be required to retrieve the stored data). This step is not required if the barograph stores continuous date and time data which cannot be altered without the fact of such alteration being automatically reported on all data printouts from its memory after such alteration, and the OO is able to verify the date and time of the takeoff and landing of the S-pA on the flight concerned.

b. AFTER THE FLIGHT

- (i) The OO shall take control of the barograph, and ensure that its seal is secure and that the barogram has the identification mark placed on it prior to takeoff. The information required in paragraph 5.1 may then be added to the chart.
- (ii) For electronic barographs, an OO must either supervise the transfer or printing of data from the barograph while it is in the S-pA, or supervise the removal of the electronic barograph from the S-pA and shall then take charge of it until the flight data is printed out. The OO then confirms that the date and time on the printout is correct and that the date and times of the altitudes and other flight data recorded and printed out correspond to the date and times of the flight concerned, and correspond with other relevant aspects of the claimed performance.

3.8 MEANS of PROPULSION/SOURCE of ENERGY EVIDENCE and CONTROL (Sub-class "Assisted" only)

3.8.1 Means of propulsion/Source of Energy evidence

The requirement to record data on the use of any non-allowed MoP/SoE may be fulfilled by any of the following methods:

Deleted: not

- a. The data is recorded by a MoP/SoE recorder, or
- b. by direct observation from the ground that the MoP/SoE has stopped, provided that there is no means of restarting it (for instance Aero-tow, car-tow etc.), or
- c. by a seal applied to the MoP/SoE in such a way that the generation of forward thrust by the MoP or the use of the SoE always results in breaking the seal.

3.8.2 MoP/SoE control methods

- a. With the use of an MoP/SoE recorder:
The MoP/SoE recorder must be sealed and opened only by an OO, and must not be accessible to pilot or crew during flight, except where it is a CIACA approved flight recorder operated in accordance with the CIACA approval.
- b. Without the use of an MoP/SoE recorder:

- (i) Before takoff, the MoP/SoE may be sealed by an OO as in 3.8.1c (and the OO shall certify that the seal was intact after landing), or
- (ii) The MoP/SoE may be rendered unusable by removing an essential part of the system (and the OO must certify that this was done).

Chapter 4

OFFICIAL OBSERVERS

4.1 AUTHORITY

4.1.1 Official Observer appointment

OO are appointed by a National Airport Control (NAC) on behalf of the FAI and CIACA.

4.1.2 OO duties

The OO shall, as the FAI and CIACA representative, control and certificate the record flight performances.

Deleted: :

4.1.3 Control and certification

a. CONTROL is the observing of takeoff, start, finish and landing and, where applicable, the timing of individual events such as declarations, sealing, installation, removal and unsealing of barographs, flight recorders and cameras, means of propulsion/Source of Energy recorders and other devices.

Deleted: ¶

Deleted: ¶

Deleted: ¶

b. CERTIFICATION is the checking of evidence and signing of appropriate certificates covering the evidence concerned.

4.1.4 Competence

OOs must be knowledgeable in the Code and have the integrity, skill and competence necessary to control and certificate S-pA flights without favour. Before being approved by the NAC, the OO should be given briefing or training appropriate to the duties of an OO.

4.1.5 Geographical area of authority

OOs are entitled to control and certificate flights of S-pA in:

- a. The country of their own NAC, and
- b. In any country and for S-pA pilots of any nationality, if the country's NAC so permits.

4.1.6 Conflict of interest

Official Observers may not act in such capacity for any record [attempt in](#) which they have any financial interest.

Deleted: attempt in

Ownership of the S-pA shall not be considered "financial interest". The essence is that monetary or other substantial gain shall not depend on the successful certification of the claim by the OO or other individual concerned.

4.1.7 Violation of duty

In case of violation of duty, the appointment of the OO shall be withdrawn. In addition, negligent certifications or wilful misrepresentations are grounds for disciplinary action by the NAC concerned.

4.2 CERTIFICATION OF EVENTS

4.2.1 General

- a. The date, times and points of takeoff and landing on the flight concerned must be verified, and there must be evidence that recording devices used for flight evidence were in the S-pA concerned during the flight.
- b. Record flights shall be certificated by the OO by completing and verifying the information in the official FAI record claim forms or, for national records, claim forms containing similar information (see 5.4).

Deleted: and badge

Deleted: or badge performances

Deleted: ¶

4.2.2 OO presence at the event

OOs may certificate individual events (such as sealing and breaking seals, installation and removal of equipment, takeoff, timing at start and finish, landing, etc.) if they were present at the event for which certification is required, or are able to satisfy themselves either through evidence from persons who witnessed the event or from other reliable sources. Evidence from air traffic control or club flying logs may be used. Barometric pressure may be obtained from the log of a nearby meteorological office.

4.2.3 Certification by non-OOs

- a. Certification of events by people other than OOs must be countersigned by an OO after verifying the statements.
- b. Air traffic controllers on duty may certificate observations of takeoffs, start and finish lines, turn and control points and landings.
- c. Outlandings may be certified by two independent witnesses who give their names, addresses, and preferably telephone numbers, if any (see 5.2).

Deleted: Possible outlandings

Chapter 5

CERTIFICATES and PROOFS

5.0 GENERAL

All certifications and calibrations must clearly relate to the flight, event, or equipment being certified or calibrated, and include the date of the certification/calibration, the signature of the person doing the certification/calibration and, where applicable, the OO's signature. Each separate sheet of paper must have this identification. Diskettes or other electronic memory devices storing flight or calibration data must be labelled clearly.

5.1 BAROGRAM

Except as permitted for flight recorders and electronic barographs (see 3.6.4 and 3.7.2), a barogram shall have the following information clearly registered on it:

- a. Identification mark of OO before takeoff,
- b. For altitude records, the pressure at ground level (QFE) at time of takeoff,
- c. Date of flight,
- d. Name of pilot,
- e. Type, serial number and altitude range of barograph, f. Type and registration of S-pA,
- g. Proof of no intermediate landing, h. Date and signature of OO after landing.

5.2 LANDING CERTIFICATE

The landing certificate shall state precisely the location of the landing place and the time of landing.

5.3 BAROGRAPH CALIBRATION CERTIFICATE

The barograph calibration certificate shall include:

- a. Type, serial number and altitude range of barograph, b. Date of calibration,
- c. Calibration trace, graph or table,
- d. Date, name and signature of calibration laboratory official.

5.4 TIMING DEVICE CALIBRATION STATEMENT

The timing device calibration statement shall include:

- a. Type and serial number of timing device used,
- b. Description of method for (and result of) calibration of the timing device (3.4.6),
- c. Date and signature of OO or calibration laboratory official doing the calibration.

5.5 FAI RECORD CLAIM FORMS

For claims submitted to the FAI, the current FAI Official Claim Forms approved by CIACA must be used. For national claims, the NAC may issue its own forms similar to the FAI versions. When submitted to the FAI, the pages of each form should be printed on one sheet of paper such as by using back-to-back printing on A3 size paper (or 11" x 17" paper in North America).

Designation	Record type	Remarks
Form A	Absolute Altitude	
Form B	Distance	
Form C	Duration	
Form E	Completed by all NACs involved	Must be included with claim file.

The FAI forms are available from the OIAOA web site <http://www.fai.org/XXXXX>, and in hard copy from the FAI office and NACs.