

FAI Sporting Code

Fédération Aéronautique Internationale

Section 7D – Class O Records and Badges

Hang Gliders and Paragliders
Classes 1 to 5

2024 Edition Effective 1st May 2024

FEDERATION AERONAUTIQUE INTERNATIONALE MSI - Avenue de Rhodanie 54 – CH-1007 Lausanne – Switzerland

Copyright 2024

All rights reserved. Copyright in this document is owned by the Fédération Aéronautique Internationale (FAI). Any person acting on behalf of the FAI or one of its Members is hereby authorised to copy, print, and distribute this document, subject to the following conditions:

- 1. The document may be used for information only and may not be exploited for commercial purposes.
- 2. Any copy of this document or portion thereof must include this copyright notice.
- 3. Regulations applicable to air law, air traffic and control in the respective countries are reserved in any event. They must be observed and, where applicable, take precedence over any sport regulations

Note that any product, process or technology described in the document may be the subject of other Intellectual Property rights reserved by the Fédération Aéronautique Internationale or other entities and is not licensed hereunder.

RIGHTS TO FAI INTERNATIONAL SPORTING EVENTS

All international sporting events organised wholly or partly under the rules of the Fédération Aéronautique Internationale (FAI) Sporting Code¹ are termed *FAI International Sporting Events*². Under the FAI Statutes³, FAI owns and controls all rights relating to FAI International Sporting Events. FAI Members⁴ shall, within their national territories⁵, enforce FAI ownership of FAI International Sporting Events and require them to be registered in the FAI Sporting Calendar⁶.

An event organiser who wishes to exploit rights to any commercial activity at such events shall seek prior agreement with FAI. The rights owned by FAI which may, by agreement, be transferred to event organisers include, but are not limited to advertising at or for FAI events, use of the event name or logo for merchandising purposes and use of any sound, image, program and/or data, whether recorded electronically or otherwise or transmitted in real time. This includes specifically all rights to the use of any material, electronic or other, including software, that forms part of any method or system for judging, scoring, performance evaluation or information utilised in any FAI International Sporting Event⁷.

Each FAI Air Sport Commission⁸ may negotiate agreements, with FAI Members or other entities authorised by the appropriate FAI Member, for the transfer of all or parts of the rights to any FAI International Sporting Event (except World Air Games events⁹) in the discipline¹⁰, for which it is responsible¹¹ or waive the rights. Any such agreement or waiver, after approval by the appropriate Air Sport Commission President, shall be signed by FAI Officers¹².

Any person or legal entity that accepts responsibility for organising an FAI Sporting Event, whether or not by written agreement, in doing so also accepts the proprietary rights of FAI as stated above. Where no transfer of rights has been agreed in writing, FAI shall retain all rights to the event. Regardless of any agreement or transfer of rights, FAI shall have, free of charge for its own archival and/or promotional use, full access to any sound and/or visual images of any FAI Sporting Event. The FAI also reserves the right to arrange at its own expense for any and all parts of any event to be recorded.

1 FAI Statutes, para. 1.6

 11
 FAI Statutes,
 Chapter 5,
 para 5.2.3.3.7

 12
 FAI Statutes,
 Chapter 6,
 para 6.1.2.1.3

Editor's Note:

The FAI Sporting Code for Hang Gliding (hang gliders and paragliders) consists of the General Section and Section 7 combined. Section 7 consists of this section and the relevant discipline subsection. In cases of doubt, consult the General Section to establish the principles before applying the specific rules which appear in Section 7.

Hang gliding (hang gliding and paragliding) is a sport in which both men and women participate. Throughout this document the words "he", "him" or "his" are intended to apply equally to either sex unless it is specifically stated otherwise.

Table of Contents

L.	INTRODUCT	FION	9
	1.1. Descri	ption	9
	,	nction	
		al Section	
		al Requirements for Hang Gliders	
	1.4.1. D	efinitions of hang gliders, as per General section	
	1.4.1.1.	Hang glider classes	
	1.4.1.2.	Types of classes	10
	1.4.2. St	tart of hang glider flight	10
	1.4.2.1.	Tow launching	10
		/heels or similar aids of take-off	
	1.4.4. P	owered hang gliders	10
	1.4.4.1.	A powered hang glider or paraglider for Delta or Paragliding badges	10
	1.4.4.2.	A powered hang glider or paraglider to claim Continental or World hang glider	gnik
	records	10	
	1.5. Flight	Definitions	11
	1.5.1. A	flight	11
	1.5.2. Q	ualifying flight	11
		light performance	
		ncompleted flight	
	1.5.5. T	ypes of flight	
	1.5.5.1.	Distance flight	
	1.5.5.2.	Goal flight	
	1.5.5.3.	Duration flight	
	1.5.5.4.	Height flight	
	1.5.5.5.	Altitude flight	
	1.5.5.6.	Gain of height flight	
	1.5.5.7.	Speed flight	
	1.5.5.8.	Free Distance Flight	12
	1.5.6. C	ourses	12
	1.5.6.1.	Declared Course	12
	1.5.6.2.	Closed circuit course	12
	1.5.6.3.	Lap	13
	1.5.7. St	tart of a flight	13
	1.5.7.1.	Launch/Take-off	13
	1.5.7.2.	Take-off place	13
	1.5.7.3.	Start Point	13
	1.5.7.4.	Start time	13
	1.5.7.5.	Start altitude	13

	1.5.7.	6. Point of Release	13
	1.5.7.	7. Start line	13
	1.5.7.	8. Ground Signal	13
	1.5.7.	9. Types of start	13
	1.5.8.	Turn point	13
	1.5.8.	1. Definition of a Turn Point	13
	1.5.8.	2. Rounding the turn point	14
	1.5.9.	Control point	14
	1.5.10.	Designated sequence	
	1.5.11.	Position checkpoint	14
	1.5.12.	Finish of flight	14
	1.5.12	2.1. The Landing	14
	1.5.12	2.2. Landing place	14
	1.5.12	2.3. Finish point	14
	1.5.12	2.4. Finish time	14
	1.5.13.	Observation Zone	14
	1.5.13	3.1. Cylindrical observation zone	15
	1.1	.1.1.1. Turn Point Cylinder	15
	1.1	.1.1.2. Start or Finish Cylinder	15
	1.5.13	3.2. FAI sector observation zones	15
	1.5.13	3.3. Section 3 observation zone	15
	1.5.14.	Claims and records publication	15
2.	FAI PRO	FICIENCY BADGES	16
	2.1. Des	scription	16
:		quirements	
	2.2.1.	Delta Bronze Badge (classes: O-1,2,4,5)	16
	2.2.2.	Delta Silver Badge (classes: O-1,2,4,5)	
	2.2.3.	Delta Gold Badge (classes: O-1,2,4,5)	16
	2.2.4.	Delta Diamonds	
	2.2.5.	Paragliding Bronze Badge	
	2.2.6.	Paragliding Silver Badge	
	2.2.7.	Paragliding Gold Badge	
	2.2.8. 2.2.9.	Paragliding Diamonds Bronze Landing Accuracy	
	2.2.9. 2.2.10.	Silver Landing Accuracy	
	2.2.10.	Gold Landing Accuracy	
	2.2.11.	Diamond Landing Accuracy	
	2.2.13.	Validity of the flights	
	2.3. Spe	ecial Conditions	18
	•	ue of Badges	
		orting Licence Requirements for Badge Flights	
3.	WORLD	AND CONTINENTAL RECORDS	19
	2.1 Gov	neral rules	10

	3.1.1. 3.1.2.	General Section Fees	
3	_	nitted Records	
J	3.2.1.	Types of Record for PG and HG	
	3.2.1.	Types of Record for PGA	
	3.2.3.	Types of Record for PG Aerobatics	
	3.2.3.1	L. Launch type distinction for PG Aerobatics	19
	3.2.4.	Minimum Increase in Flight Performance	20
	3.2.4.1	L. Distance flight	20
	3.2.4.2	2. Accuracy flights	20
	3.2.4.3	3. Aerobatics flights	20
	3.2.4.4	l. Equal result	20
	3.2.5.	Classification of Records	20
3	.3. Spe	cial Requirements	20
	3.3.1.	Advance notice	20
	3.3.2.	Exceptions	21
	3.3.2.1	L. FAI First Category event	21
	3.3.2.2	P. FAI sanctioned Accuracy competitions	21
	3.3.2.3	3. Aerobatics records	21
	3.3.3.	Breaking records	21
	3.3.4.	Task Declaration	21
3	.4. Add	itional Conditions	22
	3.4.1.	Triangle Courses	
	3.4.2.	Remote take-off and/or landing point	
	3.4.3.	Altitude differential in record and badge flights	
	3.4.3.1	1	
	3.4.3.2	•	
	3.4.3.3	3. Aerobatics	23
3	.5. Con	tinental Records	
	3.5.1.	Administration	
	3.5.2.	Principles	
	3.5.3. 3.5.4.	EligibilityQualifying Flights	
	3.5.4.1		
	3.5.4.2		
4.	TARLEO	F CERTIFICATES AND PROOFS – SOARING FLIGHTS	
4 . 5.		L AND MEASUREMENT OF FLIGHTS	
5	.1. Spe	cial Rules for Hang Gliders & Paragliders	2F
_	•	asurement	
	5.2.1.	Measurement of distance	26
	5.2.2.	Measurement of speed.	
	523	Measurement of altitude	26

5.2.4.	Measurement of time	26
5.2.5.	Validation Using Start, Turn or Finish Cylinders	26
5.2.6.	Measurement of accuracy	
5.2.7.	Measurement of aerobatics	27
5.3. A	ltitude Distance Relationship	27
5.4. G	PS, Flight Recorders and Barographs	27
5.4.1.	The GPS	27
5.4.	1.1. GPS Data	28
5.4.	1.2. Essential Data	28
5.4.2.	GPS and Flight Data Recorder Verification Software	28
5.4.	2.1. GPS Verification procedures	28
5.4.3.	The barograph	28
5.4.4.	Flight data recorders	
5.4.5.	Aero tow launches	29
6. HANG	GLIDERS FITTED WITH A POWER SOURCE	30
6.1. P	rinciple of Use	30
6.1.1.	Records and Badges	30
6.1.2.	Power source recorder	30
7. TASK [DECLARATION FORM	31
7.1. S	OARING TASK DECLARATION FORM	31
7.2. A	EROBATICS TASK DECLARATION FORM	25 -
8. OFFICI	IAL OBSERVERS	27 -
8.1. A	uthority	27 -
8.2. R	egister	27 -
	Qualifications	
	ontrol	
	ertification	
8.6. Si	uspension or Cancellation of Authority	27 -
	NCE CALCULATION	
10. GUI	DELINES FOR CLASS II & V DETERMINATION	29 -
10.1.	Background	29 -
10.2.	Classification Procedures	
10.3.	Fairings	29 -
11. GLO	DSSARY OF TERMS AND ABBREVIATION	30 -

1. INTRODUCTION

1.1. Description

Section 7 of the Sporting Code deals with records, proficiency badges, World and Continental Championships for hang gliders and paragliders in all classes.

1.2. Conjunction

Section 7 is to be used in conjunction with the General Section (GS) of the Sporting Code. In the event of ambiguity the General Section takes precedence. For ease of reading and to allow the various disciplines covered by Section 7 to develop individually it is split into multiple sub-sections:

Discipline specific subsection:

Common. Common rules and recommendations for all Category 1 and Category 2 events across all Hang gliding and Paragliding disciplines.

7A. Hang Gliding (Classes 1, 2, 4, 5) and Paragliding (Class 3) Cross Country.

7B. Paragliding (Class 3) Aerobatics.7C. Paragliding (Class 3) Accuracy.

7D. Records and Badges (all Classes).

Note: Separate sub-sections may be created in future for sub-disciplines such as aerobatics and speed gliding if a regular and viable sequence of Category 1 events develops.

1.3. General Section

The following subjects are detailed in the General Section.

FAI authority - responsibilities (Chapter 1)
Definitions (Chapter 2)
Penalties - protests (Chapter 5)

Sporting Licences (Chapter 8)

Appeals before FAI (Chapter 9)

The General Section also contains the general principles for the following:

(7)

Sporting Events (3)
Observers and Officials (4)
World Records (6)
Flight Measurement and Control

This Section 7D deals with details of these subjects, which are specific to hang gliders and paragliders.

1.4. General Requirements for Hang Gliders

1.4.1. Definitions of hang gliders, as per General section.

A glider capable of being carried, foot launched and landed solely by the use of the pilot's legs.

1.4.1.1. Hang glider classes

Class 1: Hang gliders having a rigid primary structure with pilot weight-shift as the sole method of control, and which are able to demonstrate consistent ability to safely take-off and land in nil-wind conditions. Subsidiary controls affecting trim and/or drag are permitted, but only if they operate symmetrically.

Class 2: Hang gliders having a rigid primary structure with movable aerodynamic surfaces as the primary method of control, and which are able to demonstrate consistent ability to safely take-off and land in nilwind conditions.

Class 3: Hang gliders having no rigid primary structure (paragliders), and which are able to demonstrate consistent ability to safely take-off and land in nil-wind conditions.

Class 4: Hang gliders that are unable to demonstrate consistent ability to safely take-off and/or land in nilwind conditions, but otherwise are capable of being launched and landed by the use of the pilots legs.

Class 5: Hang gliders having a rigid primary structure with movable aerodynamic surfaces as the primary method of control in the role axis and which are able to demonstrate consistent ability to safely take-off and land in nil-wind conditions. No pilot fairings are permitted. No pilot surrounding structures are permitted, apart from a harness and control frame.

Note: Pilot fairings are defined in 10.3 below.

Note: For the purposes of demonstration, "nil-wind" shall mean a headwind of less than 1 m/s (3.6 km/h; 2.2 mph).

1.4.1.2. Types of classes

For record purposes there are five classes: 1, 2, 3, 4 and 5. Class 5 gliders may set records in both Class 2 and Class 5.

1.4.2. Start of hang glider flight

A hang glider flight shall start by foot launch from a hill or by means of mechanical equipment (aero-tow, winch launch, etc.) except that:

1.4.2.1. Tow launching

For competitions where launching is by tow, wheels, including those which are dropped immediately after take- off, may be permitted by the organisers provided it can be demonstrated that the hang glider complies with 1.4.1.

1.4.3. Wheels or similar aids of take-off

Wheels or similar aids to take-off and landing are permitted for permanently disabled pilots, provided that non- disabled pilots can fly the glider without them.

1.4.4. Powered hang gliders

1.4.4.1. A powered hang glider or paraglider for Delta or Paragliding badges

A powered hang glider or paraglider may be used to obtain Delta or Paragliding badges provided it complies with 1.4.1 and there is proof that the power source was not operated during the qualifying part of the flight performance.

1.4.4.2. A powered hang glider or paraglider to claim Continental or World hang gliding records

A powered hang glider or paraglider may be used to claim Continental or World hang gliding records provided that it complies with 1.4.1 and there is proof that the power source was stopped prior to the start point and was not capable of being restarted in flight.

1.5. Flight Definitions

The word "hang glider" covers all classes. These definitions take precedence over the ones given in the General Section.

1.5.1. A flight

A flight by a hang glider starting at take-off (1.5.7.1) and ending with the landing (1.5.12.1).

1.5.2. Qualifying flight

That part of a flight, in which the hang glider is not towed, carried or assisted by another aircraft or separate external or jettisonable power source.

1.5.3. Flight performance

The achievement attained during qualifying flight.

1.5.4. Uncompleted flight

A flight is deemed to be uncompleted if:

An accident occurs during the flight resulting in the death of any member of the crew within 48 hours, or;

Any part of the hang glider or its equipment is shed or jettisoned other than permitted jettisonable equipment, ballast or fuel declared in advance.

1.5.5. Types of flight

1.5.5.1. Distance flight

A flight measured for straight-line distance between either a take-off place (1.5.7.2) or a start point (1.5.7.3) and a finish point (1.5.12.3).

1.5.5.2. Goal flight

A flight from a start point to a finish point specified in writing before take-off. A goal flight may be measured for distance and/or speed.

1.5.5.3. Duration flight

A flight timed from take-off to landing. Landing must be completed by twilight or sunset time, according to local air laws (night flying is prohibited).

Note: FAI does not recognise duration as a category for hang glider records.

1.5.5.4. Height flight

A flight measured for height achieved or maintained. Height is defined as the vertical distance from the take-off place or release from tow.

Note: FAI does not recognise height flight as a category for hang glider records.

1.5.5.5. Altitude flight

A flight measured for altitude achieved or maintained. Altitude is defined as the vertical distance from mean sea level.

Note: FAI does not recognise altitude flight as a category for hang glider records.

1.5.5.6. Gain of height flight

A flight measured for gain of height between any low height and the subsequent greatest height during qualifying flight.

1.5.5.7. Speed flight

A flight timed for speed between a start point and a finish point, possibly around one or more turn points, specified in writing before take-off.

1.5.5.8. Free Distance Flight

The Start Point and position checkpoint(s) of free distance record flight performances may be declared post flight. The free distance record types are:

- Free distance: a flight from a start point to a finish point with no position checkpoint.
- Free out and return distance: a closed course flight having one position checkpoint.
- Free distance using up to 3 position checkpoint: a flight from a start point via up to 3 position checkpoints to a finish point. Only the position checkpoint must be at least 10 kilometres apart and may be claimed only once.
- Free distance around a triangle:
- a closed course flight via 3 position checkpoints, independent of the position of the start/finish point. The official distance is given by the sum of the legs of the triangle formed by the position checkpoints.
- a flight around 2 position checkpoint with return to the start/finish point
- the start/finish point is not position checkpoint unless specifically declared as such.

1.5.6. Courses

A course consists of the straight line(s) between a start point and a finish point via any turn or control points in the designated or pre-declared sequence. A closed course may involve one, two, or three intermediate turn points.

1.5.6.1. Declared Course

A course declared in advance in writing by the pilot.

1.5.6.2. Closed circuit course

- Out-and-return Flight: A flight to a turn point with return along the reciprocal course to the start/finish point.
- Triangular Course: a flight around 2 turn points with return to the start/finish point. For badges, there are no constraints on the shape of the triangle, but for records there are. See 3.4
- Polygon Course: A flight around a course with 3 or more turn or control points and with return to the start point. Note: FAI does not recognise the polygon course as a category for records, but they may be used for badges where verified by OLC rules.

1.5.6.3. Lap

A single completed flight around a closed circuit course. A flight may include more than one lap of a course.

1.5.7. Start of a flight

1.5.7.1. Launch/Take-off

The point and/or time at which all parts of the hang glider or its crew cease to be in contact with or connected to the ground or water.

1.5.7.2. Take-off place

The point from which the take-off is made. If operating from an airfield, the point may be taken as the center of the airfield.

1.5.7.3. Start Point

The take-off place; or the point of release of tow; or the crossing of a start line; or departure from a cylinder observation zone recorded by a GPS or an approved flight recorder.

1.5.7.4. Start time

The time of the hang glider at the start point.

1.5.7.5. Start altitude

The altitude of the hang glider above sea level at the start point.

1.5.7.6. Point of Release

The place vertically below the hang glider when it releases from a tow.

1.5.7.7. Start line

A gateway of a designated width and height, the base being specified on the surface.

1.5.7.8. Ground Signal

A ground signal may be used to indicate the start of a task or section of a task. A ground signal may be a start point or a control point.

1.5.7.9. Types of start

Flying Start. The hang glider is in qualifying flight when crossing the Start point. Standing Start. A start by a stationary hang glider timed from the giving of a "go" signal.

1.5.8. Turn point

1.5.8.1. Definition of a Turn Point

GPS coordinates, which are precisely specified before take-off.

1.5.8.2. Rounding the turn point

A turn point is rounded when the entire hang glider is proved that the designated observation zone has been entered. See 1.5.13.

1.5.9. Control point

A control point is a point, which the hang glider is required to over-fly or to land at during a flight along a course.

1.5.10. Designated sequence

The order in which the turn or control points shall be flown.

1.5.11. Position checkpoint

A position checkpoint is a point with GPS coordinates, which the pilot proves to have over-flown during a flight of which the route has not been declared in advance.

1.5.12. Finish of flight

1.5.12.1. The Landing

The point and/or time at which any part of the hang glider or its crew

- First touches the ground.
- Comes to rest after landing.

1.5.12.2. Landing place

Either the centre of the airfield or the precise place with GPS coordinates, at which the landing is made.

1.5.12.3. Finish point

Either:

- The landing place
- The entry of an observation zone (or optionally a sector, if a flight data recorder is used instead of a GPS).
- For free distance and free distance using up to 3 position checkpoint flights (1.5.5.8) the furthest point flown, measured from the take off or start point.
- For Closed course flight finish point is same as start point.

1.5.12.4. Finish time

The time at which the glider reaches the finish point.

1.5.13. Observation Zone

The zone which it must be proved that the glider entered in order to validate a start point, turn point or finish point. These may be either the FAI Observation Zones (FAI sectors) specified in the General Section or as defined below.

If the flight performance is validated by GPS, a cylindrical observation zone shall be used. If an approved IGC flight data recorder is used, a cylindrical observation zone is preferred, but a FAI sector, as defined in Section 3 (Gliders) of the Sporting Code, as reproduced below in 1.5.13.3,may be used.

1.5.13.1. Cylindrical observation zone

A turn point cylinder may be specified by GPS coordinates and radius. The record or badge distance will be the minimum distance it is possible to fly by entering the specified observation zones. For badges and records, the radius of the turn point shall be 400m equally all around the turn point coordinates.

1.1.1.1.1. Turn Point Cylinder

A cylinder of 400m radius around a set of GPS co-ordinates.

1.1.1.1.2. Start or Finish Cylinder

A cylinder of 400m radius around a set of GPS co-ordinates. Larger radii might be used in competitions; see Section 7A – Class O.

1.5.13.2. FAI sector observation zones

A sector observation zone is the airspace above a 90-degree sector of a cylinder with its apex at the waypoint. This sector is:

- a) For a turn point: symmetrical to and remote from the bisector of the inbound and outbound legs of the turn point,
- b) For a start point: symmetrical to and remote from the outbound leg,
- c) For a finish point: symmetrical to and remote from the inbound leg.

1.5.13.3. Section 3 observation zone

This observation zone is the airspace above a 90-degree sector with its apex at the waypoint. This sector is:

- a) For a turn point, symmetrical to and remote from the bisector of the inbound and outbound legs of the turn point,
- b) For a start point, symmetrical to and remote from the outbound leg,
- c) For a finish point, symmetrical to and remote from the inbound leg.

1.5.14. Claims and records publication

3D track-logs in IGC format must be submitted with all claims. They will be published on the FAI/CIVL website along with the claims. All records will be published along with their track-logs.

2. FAI PROFICIENCY BADGES

2.1. Description

FAI proficiency badges are standards of achievement, which do not require to be renewed. They are intended to provide a graduated scale of difficulty to measure and encourage the development of a pilot's flying skill, particularly in cross-country flying.

The Bronze badge should be achievable by most pilots within the first year of active flying and landing accuracy, with the silver following in the next year or two. The gold badge should be achievable for most pilots within the first five years of cross country flying. The diamond badge should be achievable by perhaps half of all pilots within ten years of flying."

"In any one year, we would expect that for advanced-rated (IPPI 4 or 5) pilots, the bronze badge distance would be flown by 100% of them, the silver badge distance would be flown by more than 75%, the gold badge distance would be flown by 50%, and the diamond badge distance would be flown by perhaps 15-25%. Results may vary from one nation to another, however the qualifications are the same in every country. Delta badges are for pilots flying hang gliders in classes 1, 2 4 and 5. Paragliding badges are for class 3. Accuracy badges are for Paragliders.

2.2. Requirements

Any type of open or closed course may be used for the distance requirement of the Delta and Paragliding Bronze, Silver and Gold badge. For the Delta and Paragliding Diamond badge, the open course may be either straight distance or distance via 3 turn points. The closed course may be out-return, or triangle of any shape.

2.2.1. Delta Bronze Badge (classes: O-1,2,4,5)

Distance 30 km
 Or Duration 1,5 hours
 Or Gain of Height 500 m

2.2.2. Delta Silver Badge (classes: O-1,2,4,5)

Distance 100 km

and Duration 3 hours

and Gain of Height 1000 m

2.2.3. Delta Gold Badge (classes: O-1,2,4,5)

Distance 150 km

and Duration 5 hours

and Gain of Height 2000 m

2.2.4. Delta Diamonds

There are three separate Delta Diamonds, which may be obtained independently from each other:

• Diamond Open Course: 300 km

Diamond Gain of Height: 3000 mDiamond Closed Course: 300 km

2.2.5. Paragliding Bronze Badge

Distance 30 km
 Or Duration 1,5 hours
 Or Gain of Height 500 m

2.2.6. Paragliding Silver Badge

Distance 75 km

And Duration 3 hours

• And Gain of Height 1000 m

2.2.7. Paragliding Gold Badge

• Distance 125 km

• And Duration 5 hours

And Gain of Height 2000 m

2.2.8. Paragliding Diamonds

There are three separate Paragliding Diamonds, which may be obtained independently from each other:

• Diamond Open Course: 200 km

Diamond Gain of Height: 3000 m
 Diamond Closed Course: 200 km

2.2.9. Bronze Landing Accuracy

Four consecutive landings within 1m of the centre of the target

2.2.10. Silver Landing Accuracy

Four consecutive landings with a total score of 1m or less

2.2.11. Gold Landing Accuracy

Four consecutive landings on the pad within 10cm of the centre of the target

2.2.12. Diamond Landing Accuracy

There are three separate Paragliding Diamonds, which may be obtained independently from each other:

- Five consecutive scores of 5cm or less
- Four consecutive landings with a combined total of 10cm or less
- Three consecutive scores of 0

2.2.13. Validity of the flights

Flights achieved before May 1st 2012 do not count for Accuracy badge.

2.3. Special Conditions

- The pilot shall be alone on the hang glider.
- For soaring badges, flights may be completed in any order and any flight may count for any badge for which it fulfils the requirements.
- For Accuracy badges, flights shall be completed in FAI sanctioned competitions, and the scores shall be validated in the final results of the competitions. Drop score is not dropped for the purpose of the record or badge achievement.

2.4. Issue of Badges

Badges shall be issued only with the pilot's NAC approval. The NAC shall keep a register of pilots' names and dates of completion of the badge flights.

Badges may be issued as follows

- The NAC orders badges from FAI and issue them to its pilots; or
- The pilot asks the NAC to approve his/her performance and pay a fee to FAI. The pilot then receives the badge from the CIVL Administrator.

2.5. Sporting Licence Requirements for Badge Flights

A sporting licence is not required for badge flights. An official observer is recommended for soaring flights, but is not required provided an acceptable validation method is used (e.g. WXC, OLC, Leonardo, etc). In Accuracy flights, the Chief or Event Judge will validate the scores, which are then included in the competition results.

3. WORLD AND CONTINENTAL RECORDS

3.1. General rules

3.1.1. General Section

See Sporting Code General Section, reference Chapter 6.

3.1.2. Fees

The FAI Secretariat charges NACs an administration fee for processing record applications, see "https://www.fai.org/record-breakers-space" for details of current charges.

3.2. Permitted Records

3.2.1. Types of Record for PG and HG

The following types of flight performance may be recognised as hang gliding and paragliding records:

- Free distance
- Straight distance to a declared goal
- Declared distance around a triangular course
- Declared distance using up to 3 turn points
- Declared out-and-return distance
- Free distance around a triangular course
- Free distance using up to 3 position checkpoints
- Free out-and-return distance
- Speed around triangular courses of 25, 50, 100, 150, and all multiples of 100 km
- Speed over out-and-return courses of 100 and all multiples of 100 km
- Gain of height

3.2.2. Types of Record for PGA

- Accuracy landing (PG only): Number of consecutive valid rounds in FAI sanctioned competitions with a score of 0
- Accuracy landing (PG only): Number of consecutive valid rounds in FAI sanctioned competitions with a score of =<5cm together with the sum of those scores measured in cm.

3.2.3. Types of Record for PG Aerobatics

- Number of Infinity tumbling rotations,
- Number of Esfera rotations,
- Number of Misty flip rotations,
- Number of Twister rotations,
- Number of Heli to SAT rotations.

3.2.3.1. Launch type distinction for PG Aerobatics

Foot launch

- Airborne launch (from helicopter, balloon, D-bag, Roll over, etc)
- Winch

3.2.4. Minimum Increase in Flight Performance

3.2.4.1. Distance flight

To be recognised as a new record all distance flights must exceed the previous record by a minimum of one kilometre, speed flights must better the previous record flight performance by 0,1 km/h the gain of height record must show an improvement of minimum of 100m.

All record achievements shell be rounded to 100m for distance and 0,1 km/h for speed. 50m or 0,05km/h is rounded up.

3.2.4.2. Accuracy flights

To be recognised as a new record all accuracy flights must exceed the previous record by a minimum of one round, or a minimum of one (1) cm.

3.2.4.3. Aerobatics flights

To be recognised as a new record all aerobatics flights must exceed the previous record by a minimum of one rotation.

3.2.4.4. Equal result

If a pilot score equals a previous record, a pilot may claim equal record.

3.2.5. Classification of Records

Records listed in 3.2.1 and 3.2.3 may be claimed in the following categories:

- General category The best performance achieved by a solo pilot.
- Multiplace category For the best performance in this category, the age of each occupant other than the designated pilot-in-command shall not be less than 14 years. Only the pilot in command need hold an FAI Sporting Licence but only holders of FAI Sporting Licences can be co-holders of a record .
- Female category The best performance achieved by a solo woman.
- Junior category The best performance achieved by a Junior pilot as per S7 Common 2.2.2. Records listed in 3.2.2 may be claimed in the following categories:
- General category The best performance achieved by a solo pilot.
- Female category The best performance achieved by a solo woman.
- Junior category The best performance achieved by a Junior pilot as per S7 Common 2.2.2.

3.3. Special Requirements

3.3.1. Advance notice

Advance notice is required for all record attempts, except at the competitions where FAI officials are present and proper arrangements have been made to control the attempt. The pilot must make the record attempt declaration to his NAC and dedicated CIVL email address (civl-declaration@fai.org) prior to taking off via email or electronic means.

3.3.2. Exceptions

Except as stated in 3.3.2.1 or 3.3.2.2., and 3.3.2.3 a GPS or flight data recorders that comply with the IGC (sporting code section 3) standards, and optionally a barograph, shall be used on all record attempts. It must show that no intermediate landing was made and generally substantiate the flight.

3.3.2.1. FAI First Category event

In FAI First Category events a barograph is not required for record and badge flights made during closed circuit tasks, which contribute to the final scores, provided the organiser agrees to provide the necessary flight documentation.

Notification of a record that has been broken during a First Category event can be sent directly to FAI. Such a notification must only include information necessary to prove that the conditions have been met. However the notification sent directly to FAI must also be sent to the record claimants NAC.

3.3.2.2. FAI sanctioned Accuracy competitions

In FAI sanctioned Accuracy competitions, the Chief or Event Judge validates the flights that contribute to record and badge attempts. The scores contribute to the final results, submitted by the organisers to CIVL. For record attempts, consecutive flight scores may be recorded across multiple competitions. The official results of all FAI sanctioned Accuracy competitions, reported as part of the WPRS, can be used to prove a pilot's flight scores are consecutive across competitions, and that he has not competed in additional sanctioned competitions in the interim.

At least one judge from the CIVL list of judges must be judging at the relevant competitions.

Notification must be received by FAI within 7 days of its completion (that starts the day the consecutiveness of the round has been broken) as a record attempt, unless an extension is granted.

3.3.2.3. Aerobatics records

For aerobatics records, there is no need to use a GPS device, but flights must follow rules as stated in 5.2.7.

3.3.3. Breaking records

Any record(s) may be broken on any flight for which the requirements are met, except that:

- On a speed flight over a triangular or out-and-return course only the record distance immediately less than the distance flown will count for a record (e.g. a flight of 207 km may break only the 200 km record).
- On completion of a flight to goal, it is permitted to continue on for straight Distance, the distance being measured from the Start Point to the furthest point flown (1.5.12.).

3.3.4. Task Declaration

For records, an official observer is required. When a record flight is to be validated by use of a GPS or flight data recorder, the task declaration must state the type of start, turn and finish points to be used e.g. FAI Sector or cylinder. If a GPS is being used to validate the flight, a copy of the task declaration must be filled out and presented to the official observer prior to the start of the flight; additionally, the pilot shall enter the course into the GPS' route table. If an IGC flight data recorder is being used, the declaration needs to be made solely in the instrument itself.


For Accuracy landing no declaration of the task is necessary.

3.4. Additional Conditions


3.4.1. Triangle Courses

For a record no side of a triangular course may have a length of less than 28% of the total distance of the course.

invalid 100-km triangle



valid 100-km triangle



3.4.2. Remote take-off and/or landing point

A pilot may take-off from a point remote from the start point and/or land at a point remote from the finish point of the flight provided that the start and finish points are declared and the pilot is properly controlled over-flying these points. Any distance flown before the start point or after the finish point is not counted towards the course distance.

3.4.3. Altitude differential in record and badge flights

The loss of height permitted between the start altitude and the finish point, regardless of method of launch, is limited as follows:

3.4.3.1. Speed and Distance flights

Speed and/or Distance flights up to and including 125 km. The loss of height must not exceed 2% of the distance flown. No claims will be accepted for flights that do not satisfy this requirement.

3.4.3.2. Speed and Distance

Speed and distance flights exceeding 125km: no time or distance penalty is applied for height differential. Where tow-launch or powered launch of any type is used, release or engine off height must not exceed 1,000m above the ground level of the place of launch.

3.4.3.3. Aerobatics

No limitation in altitude/height at which the manoeuvre can be started. For safety reasons, the minimum height at which the manoeuvre must be completed is:

- Misty flips, Twister and Heli to SAT: 200 m AGL
- Infinity tumbling and Esfera: 400 m AGL

3.5. Continental Records

3.5.1. Administration

Record homologation is to be carried out by the FAI Secretariat and fees should be set by the Secretariat in line with those currently charged for World Records. The claim process for Continental Records shall be the same as the current procedure for claiming World Records.

Both World and Continental record can be claimed on one form.

3.5.2. Principles

- The time limits, process and proofs required for record claims shall be the same as is currently the case for World Records.
- Continental Records shall be available for the same categories and types of flight performance as currently exist for World Records.
- The appeals process for dealing with record disputes should be the same as for World Records.
- Continental Records shall only be permitted for the continental regions specified in the General Section.
- The first date on which continental records may be set is 1st May 2009.

3.5.3. Eligibility

Only pilots who have an FAI Sporting Licence issued by a nation which is a part of a particular continental region may set a Continental Record for that continental region.

3.5.4. Qualifying Flights

3.5.4.1. Where Flown

Continental Records may only be claimed for flights which start within the continental region for which the record is claimed and the majority of the flight is made within that continental region. This rule does not apply for Accuracy and Aerobatics records.

3.5.4.2. Flight Performance

Minimum flight performance for the initial continental record in any category or type shall be:

- i. Where a world record has been previously homologated in any continental region by a pilot from that region the minimum flight performance for any subsequent record must exceed that of the previously homologated world record.
- ii. Above the flight performance level of any existing national record set in that continent before the introduction of continental records and notified to the FAI Secretariat by 1st April 2009. These are published on the FAI/CIVL website.
- iii. Where no performance is recorded for a given record category and type, the CIVL Bureau may set a minimum level and these are also published on the FAI/CIVL website.

4. TABLE OF CERTIFICATES AND PROOFS – SOARING FLIGHTS

THE FOLLOWING CERTIFICATES, PROOFS AND INFORMATION ARE REQUIRED FOR RECORDS AND FAI SILVER AND GOLD BADGES AND DIAMONDS

Information required	Claim Statement	Evidence of take-off and start	Declaration of goal and turn points	Evidence of reaching each turn point	Evidence of landing or arrival at goal	Barogram or printout of GPS altitude plot	Barogram Calibration	GPS or Flight Recorder
Date of flight	Х	Х	Х	X	Х	Х		
Name of pilot and address	Х	Х	Х	Х	Х	Х		
Nationality	Х							
Type, category and class of record or badge	Х	Х	X	Х	Х			
Performance claimed	Х							
No. & expiry of FAI Licence	Χ							
Type & Number of glider	Х	Х	Х	Х	X	Х		
Type & Number of barograph						Х	Х	Х
GPS Calibration certificate							Х	
No intermediate landing						Х	Х	X
Take-off place	Х	Х						
Start point	Х	Х	Х					
Start altitude		Х						
Start time	Х	Х						
Type of launch or tow	Х	Х						
Certificate of aero tow release		Х						
Goal and turn points	Х		Х	Х	Х			
Time of declaration of above				Х				
Time of landing at goal, or finish time	X X				Х			
Landing place, if not a goal	Х				Х			
Altitude at finish point	Х				Х			
Distance	Х							
Distance penalty (if any)	Х							
Date & signature of pilot	Х		Х					
Date & signature of calibration laboratory official(2)							Х	
Date & signature of official observer	Х	Х	Х	Х	Х	Х		
Name & sex of passenger(s)		Х	Х					
Age declaration signed by passenger (s)	Х							
Tracklog in IGC format						1		X

⁽¹⁾ Altitude (record claims only)

NB: For Accuracy Badge & Record claims, the proofs required are: A copy (photocopy or scan) of the Official Scoring sheets signed by the pilot and the Chief/Event Judge, and an electronic copy of the final results file sent to the CIVL Competition Coordinator. Badge & Record claims should be made on the PG Accuracy Application form supplied in chapter 7 below.

⁽²⁾ Not required for GPS or IGC flight data recorder

Signature of Official Observer with declaration of freedom of interest in the claim.

5. CONTROL AND MEASUREMENT OF FLIGHTS

GS references: chapter 4 - Observers - Officials, chapter 7 - Measurement Requirements

5.1. Special Rules for Hang Gliders & Paragliders

Control of flights shall be effected by official observers except that aero tow pilots may certify the altitude, time and point of release from tow. Official observers are required for all record attempts, and are recommended for badge flights.

Evidence of the landing place shall be taken from the GPS or IGC flight data record track-log, and optionally additionally by witness statement if that witness is an FAI Observer.

For Accuracy flights, control is effected by the Organiser and Chief or Event Judge. No additional observers are required.

5.2. Measurement

The following requirements apply to all flights for records and proficiency badges:

5.2.1. Measurement of distance

For all records and for badge flights, distances shall be measured by GPS or approved flight data recorder. In this case, the GPS datum used shall be WGS84 and the earth model shall be the WGS84 Ellipsoid. See General Section.

5.2.2. Measurement of speed.

The average speed of the flight is the total minimum course distance divided by the elapsed time from the start point to the finish point. See 5.2.4.

5.2.3. Measurement of altitude

Altitude and altitude gain shall be by barograph, or by a GPS or flight data recorder with barometric altitude encoding in the tracklog (3D). A tracklog recording interval not exceeding 1 second shall be used.

5.2.4. Measurement of time

Where a GPS or approved flight data recorder is used to validate a flight and the track-log has 2 points either side of the start or goal line (or cylinder circumference) at most 1 seconds apart, then the start or finish time is interpolated from these points (constant speed being assumed).

5.2.5. Validation Using Start, Turn or Finish Cylinders

The record or badge distance shall be calculated as the minimum distance it is possible to fly by entering the cylinder observation zones. See 1.5.13.3.1. The minimum distance is defined as the straight-line distance between each pair of turn points, decreased by 800 meters for each **turn point** and 400 meters for each **Start/Finish point**.

5.2.6. Measurement of accuracy

For all records and for badge flights, accuracy scores shall be measured by a measuring device according to as specified in Section 7C – Class O, Paragliding Accuracy CLASS 3 (4.3. Automatic Measuring Device), during valid rounds flown in an FAI sanctioned competition (Cat1. or Cat 2) and accepted by the judge(s) included in the official results submitted for that competition.

Only flights achieved on a measuring device with a 2cm DC will count towards records and badges. Flights done on a 3cm or larger DC measuring device will not be counted and will break consecutiveness if pilot competes in such a competition.

5.2.7. Measurement of aerobatics

Altitude shall be measured by barograph, proving that the manoeuvre was stopped at or above the minimum prescribed altitude. See 3.4.2.3. for minimum altitudes.

Video footage from at least 2 (two) different points of view, one of which must point to the pilot and show his action during the entire execution of the flight. The cameras must be used in a way that the manoeuvres and rotations are clearly visible and countable from either of the cameras. Video footage must not be edited, cut or in any other way manipulated and must show record flight from the start of the flight.

5.3. Altitude Distance Relationship

For allowable height loss during record and badge flights see item 3.4.2

5.4. GPS, Flight Recorders and Barographs

A serviceable GPS or approved IGC flight recorder, and optionally a barograph must be used for all badge and record flights. The GPS or flight recorder must record altitude in the track-log (i.e. the track-log is 3D); alternatively, a non-altitude-encoding GPS (i.e. a 2D track-log) may be used if supplemented by a barograph; however, no barograph is required with a 2D GPS for the bronze badge.

5.4.1. The GPS

A GPS track-log with altitude encoding (3D) may be used to validate a claim for a badge or record flight providing the track-log is nearly continuous and provides unequivocal evidence that no intermediate landing was made and it generally substantiates the flight. Interruptions in the track-log will not invalidate the flight provided the gaps do not bring into question the continuity of the flight. Generally speaking, gaps of less than 10 min. are acceptable. GPS units without altitude encoding (2D) may be used alone only for bronze badges; for silver and higher badges, and records, 2D GPS may only be used in combination with a barograph.

- The GPS data (for record attempts) shall be downloaded by the Official Observer using flight verification software (see 5.4.2 below) that reads the GPS directly, produces an IGC formatted file and incorporates a security feature to identify tampering.
- The Official Observer must clear the active GPS track-log before the start of the flight. The GPS memory should contain the start point, any turn points and the declared finish point (in addition to any other points) before the start of the flight. The route, if any, should be activated in the GPS and so observed by the Official Observer at the start of the flight.
- The recording interval of the GPS, if adjustable, should be set to an interval as short as feasible, taking into account the memory capacity of the GPS and the intended length of flight, but in any event equal or less than 1s.

5.4.1.1. GPS Data

The pilot must provide an unambiguous track-log that shows without doubt that the data was collected;

- By the pilot of the hang glider on the flight in question.
- Of the declared turn point co-ordinates from the correct location in the correct sequence.
- Between the take-off and landing.
- With all relevant information being present on the track-log.

5.4.1.2. Essential Data

The track-log must show for any start, finish or turn point that the pilot was in the relevant observation zone i.e. one of the following:

- A point within the normal FAI sector or cylinder.
- A pair of consecutive points not more than 1 seconds apart for which a straight line drawn from
 the first point to the second point passes through the allowable sector, plus the allowable sector
 additions for possible GPS error.

5.4.2. GPS and Flight Data Recorder Verification Software

The verification software must confirm that all points used to verify the flight occurred at reasonable times (e.g. on the day in question, between the start of the task and the end of the task, and showing the correct chronology of start and turn points). It must also have an integral security feature (often known as the G Security Record) which will indicate if a track-log has been tampered with at any point since recording. It is the responsibility of the NAC controlling the record attempt to provide evidence of this security to the FAI, that is, an electronic copy of the secured track-log, in FAI/IGC format.

5.4.2.1. GPS Verification procedures

- Pre-flight procedures are outlined in 5.4.2.
- Post-flight, the Official observer shall take control of the instrument and download, or observe being downloaded, the track-log and the declared turn points. It is recommended to use a purpose-built program like GPSDump, SeeYou or MaxPunkte for this purpose. The observer should then observe the pilot add personal information like name, birth date, start location, glider type, and save the file in a .igc format, ensuring that the G Security record is added.
- The official observer should then test the integrity of the data file with the appropriate validation program (often available with a name similar to vali.exe).
- The observer should now confirm that the pilot entered the observation zone for each turn point. This can be done by simply observing whether the closest track log point is within 400m of the turn point. Alternatively, open the track-log data file with a flight planning and analysis program like CompeGPS, SeeYou or StrePla. The observer should then add waypoints for the task (by downloading them from the instrument), and confirm that the pilot's flight course passed within the observation zones.
- Now the task distance can be calculated, by taking the shortest distance that the pilot must fly. For a speed flight, the elapsed time en route is divided by this task distance.
- Altitude calibration is not required for GPS or flight recorders.

5.4.3. The barograph

If used, the barogram produced by the barograph should endeavour to show that no intermediate landing was made and must generally substantiate the flight. A barogram by itself may not be used to validate a distance measurement.

- It must not be possible to adjust the recording function of the barograph in any way without breaking the seal or the possibility of this being apparent to the Observer
- The barograph must be sealed and opened only by an Official Observer who must observe the print out taking place on electronic barographs
- The barograph must be calibrated not more than 12 months before or one month after the record attempt.
- Calibration is not required for badge flights.

5.4.4. Flight data recorders

GPS units are the preferred instrumentation. However, flight data recorders that comply with the IGC (sporting code section 3) standards may be used. In that case, the pilot should consult Section 3 for further guidance on procedures, since they are slightly different than those for GPS.

5.4.5. Aero tow launches

To aid determination of the start altitude, the glider pilot (and the tug pilot when a barograph is on board) must ensure that a low point or "notch" is indicated on the barogram immediately following release.

6. HANG GLIDERS FITTED WITH A POWER SOURCE

6.1. Principle of Use

A hang gliding record may only be obtained if the power source, after being stopped, CANNOT be restarted in flight. This causes the pilot to fly as a genuine glider pilot with all the disciplines involved. If the engine is merely stopped but can be restarted during the flight in order to get out of trouble, the pilot is not subject to the disciplines of flying a glider and therefore has an advantage.

6.1.1. Records and Badges

For records and badges, the use of a motorised hang glider for FAI gliding record flights may be claimed provided there is proof that the power source prior to take-off was made incapable of being restarted in flight and that requirements, below, are fulfilled.

- Distance, speed and goal flights. No record or badge may be claimed unless the start line is crossed with the power source stopped.
- Height flights. No record or badge may be claimed unless a GPS, or flight data recorder or barograph, is carried and there is proof that the power source was stopped prior to the start of the height gain.

6.1.2. Power source recorder

Many flight data recorders or barographs are or can be fitted with a recorder to indicate when the power source is being operate; however for record attempts, flight data recorders that comply with the IGC (sporting code section 3) standards will be used.

7. TASK DECLARATION FORM

7.1. SOARING TASK DECLARATION FORM

Fill this form (paper, SMS, email, etc) and present it to the official observer prior to the start of the flight. If using a GPS or flight data recorder, also record the course in the instrument itself prior to the flight.

Task:

 ${\sf Class}\,({\sf O-1,2,3,4,5}); {\sf Category}\,({\sf G,F,M}); {\sf Description}\,({\sf e.g.}\,25\,{\sf km})$

Date & Time:

Time of declaration must be before the flight start (for records only; badge flights need not be pre-declared)

Pilot:

Name & signature

Glider:

Class, make, model and serial number

Take-off and Start Pt.:

Description & Coordinates: (e.g. FAI Start Point or Cylinder)

Turn Pt. 1:

(If applicable, description & Coordinates: (e.g. FAI Turn Point or Cylinder with 400m radius)

Turn Pt. 2:

(If applicable, description & Coordinates: (e.g. FAI Turn Point or Cylinder with 400m radius)

Turn Pt. 3:

(If applicable, description & Coordinates: (e.g. FAI Turn Point or Cylinder with 400m radius)

Finish Pt.:

(If applicable, description & Coordinates: (e.g. FAI Finish Point or Cylinder with 400m radius)

Official Observer:

Name, date & signature (O.O. is required for record flights, and is recommended for badge flights)



Fédération Aéronautique Internationale Application Form for Soaring Flight Badge & Record Claims

	Type of Record: World □	Continental	
	Please print clearly!		
		Sex	
A SAN			
$\mathbf{E} \mathbf{A} \mathbf{I}$			
$ \Gamma \Lambda 1 $	NAC member N°		
	FAI Sporting Lic. N°		
	CIVL ID:	Class 3 Category:	(Gen. or Fem.)
READ THIS NOW!	NOTES & INSTRUCT	TIONS REA	ND THIS NOW!
General: The current FAI Sporting C			
gliders Class 1,2,3,4, & 5 and should I Evidence: While it is desirable that al		•	
contain all relevant information and			
OFFICIAL OBSERVER CERTIFICATE (F			
Name of chief controlling official obs	•		
O.O. N°: O.O. Address:			
I certify I am satisfied with the veraci		t's documentation, and request th	at the NAC and/or FAI
process the record or badge claim. C			
Signature:			
FLICHT DETAILS (Described for all flied			
FLIGHT DETAILS (Required for all flight) Date of flight: Place Pla			
Type of take-off (foot, aerotow, wind			
other):			
Glider type & serial N°:			
PASSENGER CERTIFICATE (Only requ			
I certify that the passenger is at least			
Passenger Name, Age, Sex:			
Passenger Address: Passenger Signature:			
1 dascriger signature			
AEROTOW / WINCH RELEASE / ENGI	NE-OFF CERTIFICATE (Required	if foot-launch takeoff not used.)	
I certify the glider was released at: (e	, ,		
at: hours at: r		ure:	
Tow pilot/driver name (print):		vehicle	
registration:			
Tow pilot/driver signature:			
BAROGRAPH CERTIFICATE (Required		ro flight O O	
I certify that I inspected the barograp			
Signature: Barograph Model, Serial N°: Logitify Linspected the barograph aff	—————— Flight Recording	N° (if applicable):	
I certify I inspected the barograph aff	ter flight; it appeared un-tamper	red with O.O.	
Signature			
GPS CERTIFICATE (Required if GPS wa			
I certify that I inspected the GPS and		nt.	
O.O. Signature		10	
GPS (Make & Model): I certify I inspected the GPS after fligl	Serial N	l h	
O.O. Signature	it, it appeared un-tampered wit	.11.	
I certify that I was present when the	flight tracklog was downloaded	using	(name of tracklog
verification program) and that it fully			
O.O. Signature			

	of the pilot at the departure				
	of the finish point is	metres AMS	SL,		
	m.				
The distance flown was					
	metres) to difference in heig				
	lot at departure point throu				irograph
clock synchronised to O.	O.'s clock, and with pilot con	nmunicating to O.O. the til	me of crossing the	e departure point.).	
ALTITUDE CLAIM (Requi	red for all claims involving ga	in of height).			
Type of claim (Silver, Go	d, Diamond, Record, Other):				
Initial low point of flight	m AMSL. S	subsequent high pt	m A	MSL.	
Difference:					
	: GPS): I certify I have examir				
on (date) :	O.O. signature:				
	MS (Required for all flights o		s).		
Claim is made for (check of	off or circle applicable catego	ry or categories):			
Free Distance:	☐ Silver (HG 100 km)	☐ Gold (HG 150 km)	□ Diamond	(HG 300 km)	☐ Record
(silver: open course)	(PG 75 km)	(PG 125 km)		(PG 200 km)	
(gold, diamond: open or	,	,		,	
closed course)					☐ Record
Distance to goal:					
Out-and-return or			Diamond	(HG 300 km)	□ Record
Triangle Distance				(PG 200 km)	
Duration	☐ Silver (3 hr)	□ Gold (5 hr)			
	(HG,PG)	(HG,PG)			
		,			
	(Course of 100, 200, or 300 k			<u> </u>	km Record
Triangle Speed (Course	of 25, 50, 100, 200 or 300 k	m)		U	km Record
HG, PG, Bronze badge		☐ Distance	e 30 km (PG, HG,	RW) or	
(open or closed course distar	ce)	Duration	n 1.5 hour or		
		☐ height g			
Claimed performance:	km DISTANC	E; and/or	km/h SPEED; _	h	:min TIME.
TURN POINT/GOAL DEC	LARATION (Required before	flight, otherwise invalid, D	ata should match	Task Declaration Fo	orm)
I declare the flight cours		g, care moe invalia. 2			,
signature:					
Takeoff Place:			Lat	°N/S;	
Long					
Start point:			Lat	°N/S;	
Long					
1st turn point:			Lat	°N/S;	
Long					
2nd turn point:			Lat	°N/S;	
Long					
3rd turn point:			Lat	°N/S;	
Long			1 -4	9NI /C.	
Finish point:			Lat	N/S;	
Long			l at	°N /C -	
	°W/E		Lat	IN/O;	
Long	w/E the GPS tracklog cleared bef	ore flight and that I took	noccassion of the	GDS after the flight	Levamined
	ce post-flight and verify that				
glider entered the obser		and turn points were round	aca in the Correct	. sequences and tildt	tile bilot 2
O O Signature	vation zones.				

START & FINISH TIME CERTIFICATE (Required only for speed tasks).

I certify that I have examined the pilot's GPS tracklog, or witnessed cross the start & finish lines, and submit the following times:

FAI Sporting Code - Section 7D, Records and Badges – 1st May 2024

Start time:	HH:MM:SS; Finish time:	HH:MM:SS; Course time:	HH:MM:SS.
O.O. Signature:			
LANDING CERTIFICATE (Requ	uired for all distance and speed flight	s).	
I certify that I landed the glid	er at (exact		
position):			
at: HH:MM (landing	time). Pilot's		
	(print), signature:		
2nd witness name, address (print), signature:		
PILOT'S STATEMENT (Requir	ed for all badge and record claims).		
required supporting evidence	e. I understand that an incomplete c	e, and I request that the NAC process the claim or incorrect application will be returned to the p ir regulations and with the FAI Sporting Code (G	residing O.O. I
Date: Pilot's	signature:		



Fédération Aéronautique Internationale Application Form for PG Accuracy Badge & Record Claims

	Type of Record: World $\ \Box$	Continental	
	Please print clearly!	_	
		Sex	
$ \mathbf{F} \mathbf{A} $	National Aero Club		
1 1 1	NAC member N° FAI Sporting Lic. N°		
		Class 3 Category: (Gen. or Fem.)	
READ THIS NOW!	NOTES & INSTRUCT		
General: The current FAI Sporting (Code (General Section and Section	on 7) defines all requirements for badges & records in han	g
		ent publications from your national aero club (NAC).	
		neets, signed by the pilot and the Chief/Event Judge, plus th	e
relevant competition results files (Ex			_
	•	hich scores count for the badge/record claim).	
Name of competition:			
Name of organiser/club:	·		
Name of Chief on French landers			
Number of valid rounds flown in the			
competition:			
FLIGHT DETAILS (Required for all flig	ghts).		
Number of consecutive flights/score	es contributing to this		
claim:			
Scores of consecutive flights recorde	ed:		
Date(s) of flights/scores:	<u>:</u>		
Type of take-off (hill/foot launch, w			
other):			
Glider make & model:		 -	
CHIEF/EVENT JUDGE DECLARATION	I (Required for each competition	with scores counting towards the claim).	
I certify that the pilot scored the abo	ove stated scores consecutively in	n valid rounds in the <i>(name)</i>	
	competition on (a	dates)	
Chief/Event Judge signature:			
ORGANISER DECLARATION (Require			
I certify that the pilot was an official			
	the results submitted to the CIVL	Competition Coordinator were approved by the Chief/Event	Ĺ
Judge			
Organiser signature:			
PILOT'S DECLARATION (Required fo	ar all hadge and record claims)		
I am submitting this claim for the fo	-		
I certify that the information on this	form is a true statement regarding	ng the scoring flights made by me, and I request that the	
		(Score Sheets and Final Results files). I understand that an	
		chief/Event Judge or Organiser. I certify that the flights were	:
made in accordance with the nation	al air regulations and with the FA	of Sporting Code (General Section and Section 7).	
Date: Pilot's signatu	ıre:		

7.2. AEROBATICS TASK DECLARATION FORM

Fill this form (paper, SMS, email, etc) and present it to the official observer prior to the start of the flight.

Task:

Class (O-3); Category (G, F, M); Description (e.g. Infinity tumbling)

Date & Time:

Time of declaration must be before the flight start (for records only)

Pilot:

Name & signature

Glider:

Class, make, model and serial number

Start Pt. and type of start:

Description & Coordinates: (e.g. London, D-bag helicopter)

Official Observer:

Name, date & signature (O.O. is required for record flights)



Fédération Aéronautique Internationale Application Form for PG Aerobatics Record Claims

FAI	Type of Record: World Please print clearly! Name, Nationality Pilot's Address National Aero Club NAC member N° FAI Sporting Lic. N°		
DEAD THIS NOW!	CIVL ID:		
READ THIS NOW! General: The current FAI Sporting Code (Generand should be read in conjunction with current Evidence: While it is desirable that all eviden information and are certified by the Official Company.	publications from your national aeroce be completed on this form, se	requirements for badges & r o club (NAC).	
OFFICIAL OBSERVER CERTIFICATE (For addit			
Name of chief controlling official observer (p	ease print):		
O.O. N°: O.O. Address:			
I certify I am satisfied with the veracity and c			
record or badge claim. O.O. Signature:			
FLIGHT DETAILS (Required for all flights). Type of claim (Infinity tumbling rotations, He Date of flight: Place of take Type of take-off (foot, winch tow, airborne, of Glider type & serial N°:	-off:		
PASSENGER CERTIFICATE (Only required for I certify that the passenger is at least 14 year Passenger Name, Age, Sex: Passenger Address: Passenger Signature:	s old. Pilot signature:		
AEROTOW / WINCH RELEASE / ENGINE-OFF I certify the glider was released at: (exact pos	sition):	nch takeoff not used.)	
at: hours at : metres Al			
Tow pilot/driver name (print): Tow pilot/driver signature:	Tow vehicle reg	istration:	
Tow phot/univer signature			
BAROGRAPH CERTIFICATE I certify that I inspected the barograph and o Barograph Model, Serial N°: I certify I inspected the barograph after flight	Flight Recording N° (if appl	icable):	
VIDEO CERTIFICATE I certify that I inspected the video from all ca Video camera (Make & Model) I certify I inspected the video after flight; it al I certify that I was present when the video of flight.	Serial N opeared un-tampered with O.O.	Signatureas not edited in any way an	d it fully supported the claimed
PILOT'S STATEMENT (Required for all record I certify that this is a true statement regardin supporting evidence. I understand that an in was made in accordance with the national air	g a flight made by me, and I reque complete or incorrect application	will be returned to the pres	siding O.O. I certify that the flight

Pilot's signature:

8. OFFICIAL OBSERVERS

8.1. Authority

Official Observers are appointed by a NAC (or its delegated National Association). They are empowered to control and certificate flights for FAI Records, Badges, Championships and Competitions in their own country and in another country if its NAC gives permission.

8.2. Register

The NAC or its National Association is responsible for keeping a register of its Official Observers, for providing briefing or instruction and ensuring that access to changes to the Sporting Code is available to them. The national register should be reviewed and updated at intervals of not more than 5 years.

8.3. Qualifications

Official Observers must know the Sporting Code General Section and Section 7 and have the integrity to control and certificate flights without favour.

Official Observers may not act as such for any flight in which they are pilot or passenger or have a personal, financial or business interest. (Owning or part owning the hang glider is not of itself considered financial interest.).

8.4. Control

Control means observing of Take-off, Departure, Finish and Landing; checking GPS, flight recorders, barographs, cameras; downloading and print-out of barographs or GPS track logs, and the signing of all certificates covering the evidence concerned for the flight. The observer must also confirm that he has identified the pilot as the individual claiming the record and that he is flying a glider of the appropriate class.

8.5. Certification

Official Observers may only certificate an event at which they were present, except that they may certificate an outlanding if they arrive soon afterwards and there is no doubt about the position of the landing.

Air Traffic Controllers on duty are considered Official Observers for observation of take-off, start and finish lines, turn and control points and landing.

Aero tow pilots may certificate the altitude, time and point of release from aero tow.

Championship officials are considered as Official Observers for a record or badge flight made during the event and for which the documentation data is used for scoring a valid task.

Independent Witnesses may certificate an outlanding in the absence of an Official Observer. They must give their names, addresses, telephone numbers and e-mail addresses (if any) and state precisely the place and time of landing.

All certificates by people other than registered Official Observers must be countersigned as correct by the Official Observers controlling the flight. If an Official Observer considers he may not be entirely free of interest in the claim he must obtain the countersignature of an independent Official Observer.

8.6. Suspension or Cancellation of Authority

The NAC may suspend or cancel the authority of an Official Observer for negligent certification or wilful misrepresentation.

9. DISTANCE CALCULATION

The preferred method of distance calculation is the GPS or approved flight data recorder, set to use the WGS84 datum and the WGS84 Ellipsoid. However, if the pilot does not have such an instrument, and the flight is less than 100 km, he may use the following calculation method as an alternative.

Either scale the distance off the map directly using a ruler, or else locate the coordinates of the two points of interest. Find a navigational software program that will calculate the distance for you, for example (http://boulter.com/gps/distance/)

10. GUIDELINES FOR CLASS II & V DETERMINATION

These guidelines are intended to provide procedures for manufacturers and the CIVL Classification Technical Committee (hereafter referred to as the *Committee*).

10.1. Background

The definition of Class 2 and Class 5 hang gliders includes the requirement that it be capable of being foot launched and landed consistently in nil wind (Refer to 1.4). The reason for this requirement is to preserve the lightweight and simple nature of the class. Weight is the ultimate factor limiting performance, so this requirement helps create a level playing field while allowing reasonable design development. In order for a glider to be classified as Class 2 or Class 5 by the Committee it must be observed to be launched and landed repeatedly in nil wind. Hang gliders with aerodynamic controls that cannot pass this requirement are Class 4 gliders.

10.2. Classification Procedures

To be eligible for Class 5 records gliders must have met the classification requirements detailed in Section 7- (Hang Gliders).

10.3. Fairings

Fairings are not allowed on Class 5 gliders. For the purposes of this document a pilot fairing is a streamlined structure rigidly attached to the glider frame, partially or fully enclosing that pilot and as much as practical the surrounding structures. The shape of the fairing is designed to minimise the contribution to the total parasitic drag of the glider, the pilot and the pilot surrounding structures. Windscreens fairing the pilot's head that are not directly attached to a helmet are not allowed.

11. GLOSSARY OF TERMS AND ABBREVIATION

This section amplifies a number of terms which are used in the main text and gives some generally accepted definitions and abbreviations relevant to air sports

Alphabetical

2D GPS GPS model whose track log does not include altitude coding.

3D GPS GPS model whose track log includes altitude coding.

Altitude The vertical distance from mean sea level (MSL). See also `QNH', and `Height'.

AMSL Above Mean Sea Level AUW All Up Weight / Mass

Barogram Record of atmospheric pressure measured by a barograph or similar instrument

Barograph A self-recording aneroid barometer

C (Temperature) - Celsius

CASI Commission d'Aeronautique Sportive Internationale (the Air Sport General Commission)

Certification The signature on and preparation of certificates and other documents concerned with the process of

flight verification with a view to validation of an FAI Flight Performance

CIVL Commission Internationale de Vol Libre, the International Hang Gliding Commission

C of A Certificate of Airworthiness

CP Control Point

Ellipsoid A three-dimensional ellipse, commonly used as an Earth model. See under WGS84 ellipsoid

FAI Fédération Aéronautique Internationale, the world air sports organisation, with its headquarters in

Lausanne

FAI Sphere This has a radius of 6371km exactly, and has a similar volume to that of the WGS84 ellipsoid.

Where this is used for distance calculation, the distance for FAI purposes shall be the length of the arc of the great circle joining given points defined by their geographical coordinates, using the same Geodetic Datum for each set of coordinates. A short paper titled "FAI Distance Calculations" giving the appropriate formulas and methodology, is available from the FAI Secretariat. Also, a small PC based

distance calculation programme is available by email from the FAI Office.

g Acceleration due to gravity (9.81 m/sec²)

G Multiple of gravity force on an aircraft under acceleration

Galileo The future European GNSS system, equivalent to the Russian GLONASS and the US GPS satellite

navigation systems

Geodesic This describes the shortest distance between two points on the surface of an ellipsoidal world

model. It is the ellipsoid equivalent to a Great Circle on a sphere. Once accurate lat/longs are available based on the same geodetic datum, the ellipsoid /geodesic distance between them can be calculated using one of a number of freeware computer programs that are commonly available. For FAI distance calculation purposes, the WGS84 ellipsoid is used (GS 7.3.1.1). A small PC-based

distance calculation program for the WGS84 ellipsoid is available by email from the FAI office.

Geodetic Datum The mathematical model of the earth (and its orientation to the earth) which is used in laying out the

positional reference system (lat/long, kilometre grid, etc) before the map projection process is used to transform the three-dimensional surface of the earth model (including topographical features and the reference grid) into a flat map sheet. Some 200 Geodetic Datums (GD) are in current use and generally were chosen for the 'best fit' of their particular mathematical model to the shape of the earth over the map area concerned. Lat/long figures, to be unambiguous, should quote the GD used which is normally given in the data at the edge of each map. The WGS 84 Datum is generally accepted as the best simple mathematical model for the <u>overall</u> shape of the earth, and is an ellipsoid with an equatorial radius of 6378.1370 km and a polar radius of 6356.7523 km, and is centred on the earth's centre and orientated to the spin axis. PC-based transformation programmes are available which convert latitudes and longitudes from those relevant to one Geodetic Datum, to WGS 84 or other Datums. Differences vary from a few metres to a few kilometres. These differences are not errors, each lat/long figure is perfectly correct, it is only the different GD (world

mathematical model) which changes the lat/long figures for a given point on the earth's surface. Therefore, for distance calculations to be accurate, the lat/longs of points at the beginning and end of the leg concerned must be with respect to the same G (see para 7.3.1.1). The calculations themselves use these standardised lat/longs, applied to a distance calculation formula based on the FAI earth model given in para 7.3.1.1. The WGS 84 Datum can be used in deriving lat/longs for long distance calculations and is used by ICAO and national aviation agencies in defining highly accurate standardised runway datums for the future use of GPS as a runway approach aid.

GLONASS Global Orbital Navigation Satellite System, the Russian GNSS system similar to the US GPS

GNSS Global Navigation Satellite System (Generic term for all systems such as the Russian GLONASS and

the US GPS)

GPS Global Positioning System (US GNSS System presently managed by the Department of Defense)

GPS (2D) GPS model whose track log does not include altitude coding.

GPS (3D) GPS model whose track log includes altitude coding.

GS The General Section of the FAI Sporting Code

Height The vertical distance from a given height datum such as the take-off place. See also `QFE', and

`Altitude'.

HG Hang Glider

Homologation The validation of a Flight Performance by an NAC or FAI for record purposes hPa Hecto Pascal

(Pressure unit, equal to a millibar)

IAS Indicated Airspeed

ICAO International Civil Aviation Organisation (HQ in Montreal, Canada) IGC International Gliding

Commission, an Air Sport Commission of the FAI

ISA International Standard Atmosphere

May See under wording

Min Minute, unit of time (UT), compared to 'arcmin' which is 1 minute of angle m/s Metres per Second

MSL Mean Sea Level
Must See under wording
NAC National Airsport Control

O (FAI Class) - Hang Gliders and Paragliders

O&R or OR Out and Return

Obligations (such as to FAI) Obligations of NACs to the FAI are listed in the FAI Statutes, search for the word

"obligations".

OO Official Observer

OZ Observation zone, the segment of airspace that a glider must enter to verify flight to a waypoint

PA Paragliding Accuracy

PG Paraglider

PHG Powered Hang Glider PPG Powered Paraglider

Proficiency Badges Badges issued by the FAI for meeting specified flight performance standards

QFE Pressure Setting which indicates zero altitude when at airfield height

QNH Pressure Setting which indicates height above sea level

Record(s) Validated flight performance greater than other validated performances Shall See under 'Wording'

Should See under 'Wording'

Soaring The utilisation of the vertical component of movements of air in the atmosphere for the purpose of

sustaining flight, without the use of thrust from a means of propulsion

Sporting Licence A licence issued by the FAI and mandatory for entrants to international competitions and world or

continental record attempts

S7 Section 7 of the FAI Sporting Code i.e. this section. Also sub-sections 7A to 7C.

Sphere See FAI Sphere
TAS True Air Speed
TL Team Leader

TP Turn Point, also see WP, Waypoint

Track-log The record of a flight produced by a GPS Track-log point The individual components of a track-log

UT UTC to the local hour convention
UTC Universal Time Co-ordinated (ex-GMT)

Validation An act of ratification or official approval. In FAI terms, the act of approving a Flight Performance (or

an element of one such as reaching a Turn Point) for FAI purposes.

Verification The process of checking and assembling evidence with a view to validating a Flight Performance

Vs Stalling Speed

WADA World Anti Doping Agency

WAG World Air Games. An international sporting event involving several FAI air sports at the same time, see

GS

WP, Waypoint A generic term for either a start, turn or finish point claimed as part of a flight performance.

WGS 84 See under `Geodetic Datum'

WGS 84 EllipsoidThis is an ellipsoidal earth model with an equatorial radius of 6378,1370 km and a polar radius of

6356,7523 km. It is centred on the earth's centre and orientated to the spin axis. It is generally accepted as the best simple mathematical model for the overall shape of the earth and is used as the Geodetic Datum in many aeronautical maps. See also under "Geodesic" and "Geodetic Datum". For distance calculations using the WGS84 ellipsoid, a small PC-based program is available by

email from the FAI Office.

Wording The use of "shall" and "must" implies that the aspect concerned is mandatory; the use of "should"

implies a non-mandatory recommendation; "may" indicates what is permitted and "will" indicates what is going to happen. Words of masculine gender should be taken as including the female

gender unless the context indicates otherwise. Italics are used for explanatory notes.

WPRS World Pilot Ranking Scheme. A CIVL designed and administered system of ranking pilots from FAI

sanctioned competition results.



PRELIMINARY NOTIFICATION OF A NEW RECORD ATTEMPT

<u>Important</u>! The National Airports Control Organization (NAC) or the Official Observer controlling the attempt <u>must</u> notify FAI of the record claim within 7 days of the completion of the flight. To ensure quick circulation of the information, we recommend that you send by fax this page to FAI at the following number: +41 21 345 1077 or by Email to <record@fai.org>

Pilot's Name :				
	tional Aero Club:			
Class : _ <u>O (Ha</u>	ng Gliders)	(1, 2, 3, 4, 5)		
Passenger's Na	me :			
	(G, F, M)			
Nationality / Na	tional Aero Club:			<u>-</u>
	ke & Model :			
	Type of records cla	imed (speed to goal	l, Performance	Date of the attempt
1°)			(km, km/h, m)	
Place/Course :				
2°)			(km, km/h, m)	
Place/Course :				
3°)			(km, km/h, m)	
Place/Course :				
Name and title	of the Official who រុ	prepared this claim t	form :	
Signature :				
Seal/Stamp (if a	any) :			